



Coal Mines in Illinois Athens Quadrangle Menard & Sangamon Counties, Illinois

This map accompanies the Coal Mines Directory for the Athens Quadrangle. Consult the directory for a complete explanation of the information shown on this map.

Mining Method

- Room & Pillar (RP)
- Room & Pillar Basic (RPB)
- Modified Room & Pillar (MRP)
- Room & Pillar Panel (RPP)
- Blind Room & Pillar (BRP)
- Checkerboard Room & Pillar (CRP)
- High Extraction Retreat (HER)
- Longwall (LW)
- Underground, Method Unknown
- Strip Mine
- Auger Mine
- General Area of Mining

Source of Mine Outline

- Final Mine Map
- Not Final Mine Map
- Undated Mine Map
- Incomplete Mine Map
- Secondary Source Map

Tipple, Shaft, Slope, Drift Locations

- Strip Mine Tipple - Active
- Strip Mine Tipple - Abandoned
- Mine Shaft - Active
- Mine Shaft - Abandoned
- Mine Slope - Active
- Mine Slope - Abandoned
- Mine Drift - Active
- Mine Drift - Abandoned
- Air Shaft
- Uncertain Location
- Uncertain Type of Opening

Mine Annotation (space permitting)

Company
Mine Name
ISGS Index No., Years of Operation

Disclaimer

Please check the Coal Section at the Illinois State Geological Survey's web site at <http://www.isgs.illinois.edu> for the most up-to-date version of these products.

Note that each quadrangle scale mined-out area map requires the use of the associated text directory for full explanation of map features and mine attributes. Also note that some quadrangles have multiple seams of mining and therefore more than one map may be available for a particular quadrangle. Please take care to check for multiple maps, as extensive mining may exist in the other seams.

The maps and digital files used for these studies were compiled from data obtained from a variety of public and private sources and have varying degrees of completeness and accuracy. This compilation map presents reasonable interpretation of the geology of the area and is based on available data. Locations of some mine features may be offset by 500 feet or more due to errors in the original source maps, the compilation process, digitizing, or a combination of these factors. These data are not intended for use in site-specific screening or decision-making. Use of these documents does not eliminate the need for detailed studies to fully understand the geology of a specific site. The Illinois State Geological Survey, Prairie Research Institute, or the University of Illinois make no guarantee, expressed or implied, regarding the correctness of the interpretations presented in this data set and accept no liability for the consequences of decisions made by others on the basis of the information presented here.

These maps were designed for use at 1:24,000. Enlarging the map may reduce accuracy, as the original scale of the source maps used to compile the outlines shown varies from 1:400 to 1:150,000, and some mine locations are known only from text descriptions. See the accompanying mine directory for the original scale of the source map used for a specific mine to check accuracy of a given portion of the map. Areas with no mines shown may still be undermined; see the unlocated mines list at the back of each mine directory.

The image of the U.S.G.S. topographic base map was projected from the original UTM to Lambert Conformal Conic.

ILLINOIS
UNIVERSITY OF ILLINOIS AT URBANA-CHAMPAIGN

ILLINOIS STATE
GEOLOGICAL SURVEY
PRAIRIE RESEARCH INSTITUTE

Prairie Research Institute
Illinois State Geological Survey
615 E. Peabody Dr.
Champaign, IL 61820

Mine Outlines Compiled by
Margaret Bargh & C. Chenoweth
1994, revised 2005 & 2017

DIRECTORY OF COAL MINES IN ILLINOIS 7.5-MINUTE QUADRANGLE SERIES ATHENS QUADRANGLE MENARD AND SANGAMON COUNTIES

Margaret Bargh and Gayla Coats



Department of Natural Resources
ILLINOIS STATE GEOLOGICAL SURVEY
1994
REVISED 2005

**DIRECTORY OF COAL MINES IN ILLINOIS
7.5-MINUTE QUADRANGLE SERIES
ATHENS QUADRANGLE
MENARD AND SANGAMON COUNTIES**

1994
REVISED 2005

ILLINOIS STATE GEOLOGICAL SURVEY
William Shilts, Chief

Natural Resources Building
615 East Peabody Drive
Champaign, Illinois 61820

Phone 1-217-244-4610
Fax 1-217-333-2830

Cover photo Track-mounted duckbill loading machine at a Peabody Coal Company mine, ca. 1915.

DISCLAIMER: The accuracy and completeness of mine maps and directories vary with the availability of reliable information. Maps and other information used to compile this mine map and directory were obtained from a variety of sources and the accuracy of some of the original information cannot be verified. Consequently, the Illinois State Geological Survey (ISGS) cannot guarantee the mine maps are free of errors and disclaims any responsibility for damages that may result from actions or decisions based on them.

The ISGS updates the maps and directories periodically, and welcomes any new information or corrections. Please contact the Coal Section of the ISGS at the address shown on the title page of this directory, or telephone (217) 244-4610.

Printed by authority of the State of Illinois/2005

CONTENTS

INTRODUCTION	1
MINING IN THE ATHENS QUADRANGLE	1
PART I EXPLANATION OF MAP AND MINE SUMMARY SHEET	2
INTERPRETING THE MAP	2
Mine Type and Mining Method	2
SOURCE MAPS	3
POINTS AND LABELS	3
INTERPRETING A MINE SUMMARY SHEET	6
REFERENCES	8
PART II DIRECTORY OF MINES IN THE ATHENS QUADRANGLE	9
MINE SUMMARY SHEETS	9
Mine Index 34	
Union Fuel Coal Company, Union No. 4 Mine	9
Mine Index 309	
Cantrall Coal Company, Cantrall Mine	10
Mine Index 412	
Peabody Coal Company, Peabody No. 51 Mine	11
Mine Index 861	
Bryan Eddy Coal Company, Eddy Mine	12
Mine Index 925	
R. & S. Coal Company, Cantrall Mine	13
Mine Index 2939	
Athens-Dawson Fuel Company, Athens No. 1 Mine	14
Mine Index 2940	
Perkins & Hughes, Perkins Mine	15
Mine Index 3358	
Barr Coal Company, Barr Mine	16
Mine Index 3359	
Sangamon Valley Coal Company, Sangamon Valley Mine	17
MINES WHOSE LOCATIONS ARE NOT KNOWN, ATHENS QUADRANGLE	18
INDEX OF MINES IN THE ATHENS QUADRANGLE	19

INTRODUCTION

Coal has been mined in 76 counties of Illinois. More than 7,400 coal mines have operated since commercial mining began in Illinois about 1810; fewer than 30 are currently active. To detail the extent and location of coal mining in Illinois, the Illinois State Geological Survey (ISGS) has compiled maps and directories of known coal mines. The ISGS offers maps at a scale of 1:100,000 and accompanying directories for each county in which coal mining is known to have occurred. Maps at a scale of 1:24,000 and accompanying directories such as this are available for selected quadrangles. Contact the ISGS for a list of these quadrangles.

These larger scale maps show the approximate positions of mines in relation to surface features such as roads and water bodies, and indicate the mining method used and the accuracy of the mine boundaries. The maps are useful for locating mine boundaries relative to specific properties and for assessing the potential for subsidence in an area. Mine boundaries compiled from final mine surveys are generally shown within 200 feet of their true position. As a result of poor cartographic quality and inaccuracies in the original mine surveys, boundaries of some older mines may be mislocated on the map by 500 feet or more. Original mine maps should be consulted in situations that require precise delineation of mine boundaries or internal workings of mined areas.

The directory serves as a key to the accompanying mine map and provides basic information on the coal mines. The directory is composed of two parts. Part I explains the symbols and patterns used on the accompanying map and the summary data presented for each mine. Part II numerically lists the mines in the quadrangle and summarizes the geology and production history of each mine.

MINING IN THE ATHENS QUADRANGLE

Mining began in this quadrangle in the early 1890s. Cantrall Coal Company opened a mine near the town of Cantrall and shortly thereafter the Athens Coal Company and the Wabash Coal Company began mining near the town of Athens. These mines in Menard County closed in the early 1920s when the mining activity moved south into Sangamon County. Mines were active in the quadrangle until the 1960s when the Eddy Mine, the last to close, ceased operation in August 1964.

Only the Springfield coal seam was mined in this quadrangle. The coal was approximately 6 feet thick and ranged from 150 to 215 feet deep. Horsebacks and clay dikes were frequently encountered and water was sometimes a problem.

PART I EXPLANATION OF MAP AND MINE SUMMARY SHEET

INTERPRETING THE MAP

The map accompanying this directory shows the location of coal mines known to be present in the quadrangle. The map, corresponding to a U.S. Geological Survey (USGS) 7.5-minute quadrangle, covers an area bounded by lines of latitude and longitude 7.5-minutes apart. In Illinois, a quadrangle is approximately 6.5 miles east to west and 8.5 miles north to south, an area of about 56 square miles. The USGS generally offers one map of mines per quadrangle. In some areas where extensive mining occurred in two or more overlapping seams, separate maps are compiled for mines in each seam to maintain readability of the map.

Mine Type and Mining Method

The mine type is indicated on the map by pattern color: green represents surface mines; red and yellow represent underground mines. The red patterns are used for areas of underground mining that are documented by a primary or secondary source map. A yellow pattern is used for cases where no map of the mine workings is available, but a general area of mining can be inferred from property maps or production figures. The patterns indicate the main mining methods used in underground mines. The methods are (1) room and pillar and (2) high extraction. The method used gives some indication of the amount and pattern of coal extraction within each mined area, and has some influence on the timing and type of subsidence that can occur over a mine.

The following discussion and illustrations of mining methods are based on Guither et al. (1984).

In room-and-pillar mines, coal is removed from haulage-ways (entries) and selected areas called rooms. Pillars of unmined coal are left between the rooms to support the roof. Depending on the size of rooms and pillars, the amount of coal removed from the production areas will range from 40% to 70%.

Room and Pillar - mining is divided into six categories:

- room-and-pillar basic (RPB, fig. 1A), an early method that did not follow a preset mining plan and therefore resulted in very irregular designs;
- modified room and pillar (MRP, fig. 1B);
- room-and-pillar panel (RPP, fig. 1C);
- blind room and pillar (BRP, fig. 1D);
- checkerboard room and pillar (CRP, fig. 1E);
- room and pillar (RP), a classification used when the specific type of room-and-pillar mining is unknown.

Blind and checkerboard are the most common types of room-and-pillar mining used in Illinois today. The knowledge of room-and-pillar mining methods gives a trained engineer information on the nature of subsidence that may occur. A more extensive discussion of subsidence can be found in Bauer et al. (1993).

High-extraction These mining methods are subdivided into high-extraction retreat (HER, Fig 1F) and longwall (LW, Fig 1G, 1H). In these methods, much of the coal is removed within well defined areas of the mine. Subsidence of the surface above these areas occurs within weeks. Once the subsidence activity ceases, the potential for further movement over these areas is low; however, subsidence may continue for several years after mining.

High-extraction retreat mining is a form of room-and-pillar mining that extracts most of the coal. Rooms and pillars are developed in the panels, and the pillars are then systematically removed (fig. 1F).

In early (pre-1960) longwall mines, mining advanced in multiple directions from a central shaft (fig. 1G). Large pillars of coal were left around the shaft, but all coal was removed beyond these pillars. Miners placed rock and wooden props and cribs in the mined-out areas to support the mine roof. The overlying rock gradually settled onto these supports, thus producing subsidence at the surface. In post-1959 longwall mines, room-and-pillar methods have been used to develop the main entries of the mine and panel areas. Modern longwall methods extract 100 percent of the coal in the panel areas (fig. 1H).

SOURCE MAPS

Mine outlines depicted on the map are, whenever possible, based on maps made from original mine surveys. The process of compiling and digitizing the quadrangle map may produce errors of less than 200 feet in the location of mine boundaries. Larger errors of 500 feet or more are possible for mines that have incomplete or inaccurate source maps.

Because of the extreme complexity of some mine maps, detailed features of mined areas have been omitted. The digitized mine boundary includes the exterior boundary of all rooms or entries that were at least 80 feet wide or protruded 500 feet from the main mining area. Unmined areas between mines are shown if they are at least 80 feet wide; unmined blocks of coal within mines are shown if they are at least 400 feet on each side. Original source maps should be consulted when precise information on mine boundaries or interior features is needed.

The mine summary sheet lists the source maps used to determine each mine outline. The completeness of map sources is indicated on the map by a line symbol at the mine boundary. Source maps are organized in five categories.

Final mine map The mine outline was digitized from an original map made from mine surveys conducted within a few months after production ceased. The date of the map and the last reported production are listed on the summary sheet.

Not a final map The mine is currently active or the mine outline was made from a map based on mine surveys conducted more than a few months before production ceased. This implies the actual mined-out area is probably larger than the outline on the map. The mine summary sheet indicated the dates of source maps and the last reported production, as well as the approximate tonnage mined between these two dates (if the mine is abandoned). The summary sheet also lists the approximate acreage mined since the date of the map and, in some cases, indicates the area where additional mining may have taken place. This latter information is determined by locating on the map the active faces relative to probable boundaries of the mine property.

Undated map The source map was undated, so it may or may not be based on a final mine survey. When sufficient data are available, the probable acreage of the mined area is estimated from reported production, average seam thickness and a recovery rate comparable to other mines in the area. This information is listed in the summary sheet for the mine.

Incomplete map The source map did not show the entire mine. The summary sheet indicates the missing part of the mine map and the acreage of the unmapped area, which is estimated from the amount of coal known to have been produced from the mine.

Secondary source map The original mine map was not found so the outline shown was determined from secondary sources (e.g., outlines from small-scale regional maps published in other reports). The summary sheet describes the secondary sources.

POINTS AND LABELS

The locations of all known mine openings (shafts, slopes, and drifts) and surface mine tipples are plotted on the map. Tipples are areas where coal was cleaned, stockpiled, and loaded for shipping.

Only openings or tipples are plotted for mines without source maps. If the precise locations of these features are unknown, a special symbol is used to indicate the approximate location of the mine.

Each mine on the map is labeled with the names of the mine and operating company, ISGS mine index number, and years of operation (if known) if space permits. A seam designation is given on maps where more than one seam was mined. For a mine that operated under more than one name, only the most recent name is generally given. When a mine changed names or ownership shortly before closing, an earlier name is listed. All company and mine names are listed on the mine summary sheet in the directory, under the production history segment.



Figure 1 Mining methods: (A) room-and-pillar basic (RPB), (B) modified room and pillar (MRP), (C) room-and-pillar panel (RPP), (D) blind room and pillar (BRP).



Figure 1 (cont.) Mining methods: (E) checkerboard room and pillar (CRP), (F) high extraction retreat (HER), (G) early (pre-1960) longwall, (H) post-1959 longwall



Figure 2 Generalized stratigraphic section, showing approximate vertical relations of coals in Illinois.

INTERPRETING A MINE SUMMARY SHEET

The mine summary sheet is arranged numerically by mine index number. Index numbers are shown on the map and in the mine listing. The mine summary sheet provides the following information (if available).

Company and mine name The last company or owner of the mine is used, unless no production was recorded for the last owner. In that case, the penultimate owner is listed. Mines often have no specific name; in these cases, the company name is also used as the mine name.

Type *Underground* denotes a subsurface mine in which the coal was reached through a shaft, slope, or a drift entry. *Surface* denotes a surface, open pit or strip mine.

Total mined-out acreage shown The total acreage of the mined area mapped, including any acreage mined on adjacent quadrangles, is calculated from the digitized outline of the mine. The acreage of large barrier pillars depicted on the map is excluded from the mined-out acreage. Small pillars not digitized are included in the acreage calculation. If the mine outline is not based on a final mine map, the acreage is followed by an estimate of additional acres that may have been mined. The estimate is determined from reported mine production, approximate thickness of the coal, and recovery rates calculated from nearby mines that used similar mining methods.

SHAFT, SLOPE, DRIFT OR TIPPLE LOCATIONS

Shaft, slope, drift, or tippie locations Locations of all known former entry points to underground mines or the location of coal cleaning, tippie, and shipping equipment used by the mine's facility are listed. The location is described in terms of county, township and range (Twp-Rge), section, and location within the section by quarters. NE SW NW, for instance, would describe the location in the northeast quarter of the southwest quarter of the northwest quarter. When sections are irregular in size, the quarters remain the same size and are oriented (or "registered") from the southeast corner of the section. Approximate footage from the section lines (FEL = from east line, FNL = from north line, for example) is given when that information is known; this indicates a surveyed location and is not derived from maps. Entry points are also plotted on the map and coded for the type of entry or tippie. A mine opening may have had many purposes during the life of the mine. Old hoist shafts are often later used for air and escape shafts; this information is included in the directory when known. The tippie for underground mines was generally located near the main shaft or slope. At surface mines, coal was sometimes hauled to a central tippie several miles from the mine pit.

GEOLOGY

Seam(s) mined The name of the coal seam(s) mined is listed, if known. If multiple seams were mined, they are all listed, although the mined-out area for each seam may be shown on separate maps. Figure 2 shows the stratigraphic section of the coal-bearing interval in Illinois, and the vertical relations among the coals.

Depth The depth to the top of the seam in the vicinity of the shaft is listed, if known. The depth is determined from notes made by geologists who visited the mine during its operation or from drill hole data in ISGS files. Depth generally varies little over the extent of a mine; however, reported depths for an individual mine may vary. Depth for surface-mined coals varies, and is usually represented as a range.

Thickness The approximate thickness of the mined seam is shown, if known. Thickness also comes from notes of geologists who visited the mine during its operation or from borehole data in ISGS files. Minimum, maximum, and average thicknesses are given when this information is available.

Mining method The principal mining method used at the mine (figs. 1A-H) is listed. See the mining methods section at the beginning of this directory for a discussion of this parameter.

Geologic problems reported Any known geologic problems, such as faults, water seepage, floor heaving, and unstable roof, encountered in the mine are reported. This information is from notes made by ISGS geologists who visited the mine, or from reports by mine inspectors published by the Illinois Department of Mines and Minerals, or from the source map(s). Geologic problems are not reported for active mines.

PRODUCTION HISTORY

Production history Tons of coal produced from the mine by each mine owner are totaled. When the source map used for the mine outline is not a final mine map, the tonnage produced since the date of the map is identified. For mines that extend into adjacent quadrangles, the tonnage reported includes areas mined in adjacent quadrangles.

SOURCE OF DATA

Source map This section lists information about the map(s) used to compile the mine outline and the locations of tipples and mine openings. In some cases more than one source map was used. For example, a map drawn before the mine closed may provide better information on original areas of the mine than a later map. When more than one map was used, the bibliography section explains what information was taken from each source.

Date The date of the most recent mine survey listed on the source map is reported.

Original scale The original scale of the source map is listed. Many maps are photo-reductions and are no longer at their original scale. The original scale gives some indication of the level of detail of the mine outline and the accuracy of the mine boundary relative to surface features. Generally, the larger the scale, the greater the accuracy and detail of the mine map. Mine outlines taken from source maps at scales smaller than 1:24,000 may be highly generalized and may well be inaccurately located with respect to surface features.

Digitized scale The scale of the digitized map is reported. The scale may be different from that of the original source map. In many cases the digitized map was made from a photo-reduction of the original source map, or the source map was not in a condition suitable for digitizing and the mine boundaries were transferred to another base map.

Map type Source maps are classified into five categories to indicate the probable completeness of the map. See discussion of source maps in the previous section.

Annotated bibliography Sources that provide information about the mine are listed, with the data taken from each source. Some commonly used sources are described below. Full bibliographic references are given for all other sources. Unless otherwise noted, all sources are available for public inspection at the ISGS.

Coal Reports Published since 1881, these reports contain tabular data on mine ownership, production, employment, and accidents. Some volumes include short descriptions made by mine inspectors of physical features and conditions in selected mines.

Directory of Illinois Coal Mines This source is a compilation of basic data about Illinois coal mines, originally gathered by ISGS staff in the early 1950s. Sources used for this directory are undocumented, but they are primarily Illinois Department of Mines and Minerals annual reports, ISGS mine notes, and coal company officials.

ENR Document 85/01, Guither, H. D., J. K. Hines, and R. A. Bauer, 1985 The Economic Effect of Underground Mining Upon Land Used for Illinois Agriculture: Illinois Department of Energy and Natural Resources Document 85/01, 185 p.

Microfilm map The U.S. Bureau of Mines maintains a microfilm archive of mine maps. A microfilm file for Illinois is available for public viewing at the ISGS.

Mine notes ISGS geologists have visited mines or contacted mine officials throughout the state since the early 1900s. Notes made during these visits range from brief descriptions of the mine location to long narratives (including sketches) of mining conditions and geology.

Federal Land Bank of St. Louis, Preliminary Reports on Subsidence Investigations Mining engineers working for the Federal Land Bank of St. Louis mapped areas of subsidence due to coal mining in the early 1930s. These reports often include county maps of mine properties with mined-out areas including shaft locations, as well as subsidence areas.

REFERENCES

Bauer, R. A., B. A. Trent, and P. B. Dumontelle, 1993, Mine Subsidence in Illinois: Facts for the Homeowner Considering Insurance: Illinois State Geological Survey, Environmental Geology Note 144, 16p.

Guither, H. D., J. K. Hines, and R. A. Bauer, 1985, The Economic Effects of Underground Mining Upon Land Used for Illinois Agriculture: Illinois Department of Energy and Natural Resources Document 85/01, 185p.

PART II DIRECTORY OF MINES IN THE ATHENS QUADRANGLE

MINE SUMMARY SHEETS

A summary sheet on the geology and production history of each mine in the Athens Quadrangle is provided. These summary sheets are arranged numerically by mine index number. Consult Part I for a complete explanation of the data listed in the summary sheet.

Mine Index 34

Union Fuel Coal Company, Union No. 4 Mine

Type: Underground Total mined-out acreage shown: 591 Production indicates approximately 31 acres were mined after the map date.

SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS

Type	County	Township-Range	Section	Quarters-Footage
Main shaft	Menard	18N 6W	36	2316 FNL, 969 FWL
Air shaft	Menard	18N 6W	36	2439 FNL, 965 FWL
Air shaft	Menard	18N 6W	35	SE SW NW

GEOLOGY

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Ave	
Springfield	203	5.6	6.1	6.0	RPP

Geologic Problems Reported: Lenticular pods of black shale up to 3 feet thick made up the roof over much of the mine. In some cases, about 5 feet of limestone was over the black shale. "Soapstone", a very clay-rich shale, was the rock above the limestone. When the limestone came down, the soapstone would also fail. One fall extended 35 feet upwards. Numerous clay veins were present in the coal, some 2 feet wide. At least one clay vein was associated with a slip where the coal was shattered for 1 foot on either side. A small fault with 1.5 feet offset was found ¼ mile east of the shaft. Pyrite lenses were present along bedding planes. The underclay floor was 7 feet of fairly soft clay, with a firmer clay below that contained boulders. The upper part heaved, especially the top 1.5 feet. The mine map shows that old works of the Athens-Dawson Mine (mine index 2939) were encountered in the southern part of the eastern extensions of this mine.

PRODUCTION HISTORY

Company	Mine Name	Years	Production (tons)
Wabash Coal Company	Wabash	1892-1898	440,852
Wabash Coal Company	Wabash No. 2	1898-1919 *	1,468,805
Union Fuel Coal Company	Union No. 4	1920-1921	203,529
Union Fuel Coal Company	Union No. 4	1922-1923	134,116 **
			2,247,302

* Abandoned 1914; idle 1915-1919

** Production after map date

Last reported production: February 1923

SOURCES OF DATA

Source Map	Date	Original Scale	Digitized Scale	Map Type
Microfilm, document 352214	2-4-1921	1:2400	1:4800	Not final
Company, state archive, PB_360	2-16-1913	1:2400	1:2400	Final

Annotated Bibliography (data source, brief description of information)

Coal Reports - Production, ownership, years of operation.

Directory of Illinois Coal Mines (Menard County) - Mine names, mine index, ownership, years of operation.

Mine notes (Menard County) - Mine type, shaft location, seam, depth, thickness, geologic problems.

Microfilm map, document 352214, reel 03138, frames 269-272 - Shaft locations, mine outline, location of old works.

Company map, state archive, PB_360 - Mine outline (eastern & southeastern).

Mine Index 309**Cantrall Coal Company, Cantrall Mine**

Type: Underground Total mined-out acreage shown: 534 Production indicates approximately 52 acres were mined after the map date.

SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS

Type	County	Township-Range	Section	Quarters-Footage
Main shaft	Sangamon	17N 5W	8	2680 FSL, 2280 FWL
Air shaft	Sangamon	17N 5W	8	2740 FSL, 2740 FWL

GEOLOGY

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Ave	
Springfield	213			6.0	MRP

Geologic Problems Reported: Coal balls were reported.

PRODUCTION HISTORY

Company	Mine Name	Years	Production (tons)
Cantrall Co-operative Coal Company	Cantrall	1890-1918 *	2,474,637
Cantrall Co-operative Coal Company	Cantrall	1918-1919	52,945 **
Sangamon Coal Company	Sangamon No. 3	1919-1922	124,514 **
Buckley Coal Company	Cantrall	1922-1923	34,265 **
Cantrall Coal Company	Cantrall	1923-1924	1,600 **
			<u>2,687,961</u>

* Idle 1916

** Production after map date

Last reported production: 1924

SOURCES OF DATA

Source Map	Date	Original Scale	Digitized Scale	Map Type
Microfilm, document 351196	8-1918	1:2400	1:4303	Not final

Annotated Bibliography (data source, brief description of information)

Coal Reports - Production, ownership, years of operation.

Directory of Illinois Coal Mines (Sangamon County) - Mine names, mine index, ownership, years of operation.

Mine notes (Sangamon County) - Mine type, shaft locations, seam, depth, thickness, geologic problems.

Microfilm map, document 351196, reel 03134, frames 360-361 - Shaft locations, mine outline, mining method.

Mine Index 412**Peabody Coal Company, Peabody No. 51 Mine**

Type: Underground Total mined-out acreage shown: 941

SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS

Type	County	Township-Range	Section	Quarters-Footage
Main shaft	Sangamon	17N 5W	27	NW SW SE
Air/escape shaft	Sangamon	17N 5W	27	NW SW SE

GEOLOGY

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Ave	
Springfield	210		5.8	5.5	RPP

Geologic Problems Reported: Horsebacks were common, sometimes pyritized and very hard. The roof was uneven due to these concretions. There were slight displacements of the coal along the horsebacks.

PRODUCTION HISTORY

Company	Mine Name	Years	Production (tons)
Cora Coal Company	Cora	1904-1915	1,425,891
Springfield District Coal Mining Company	Springfield District No. 1	1915-1918	628,437
Springfield District Coal Mining Company	Springfield District No. 51	1918-1925	638,993
Peabody Coal Company	Peabody No. 51	1925-1934	<u>1,880,776</u>
			4,574,097

Last reported production: March 1934

SOURCES OF DATA

Source Map	Date	Original Scale	Digitized Scale	Map Type
Microfilm, document 351231	3-9-1934	1:2400	1:4138	Final

Annotated Bibliography (data source, brief description of information)

Coal Reports - Production, ownership, years of operation.

Directory of Illinois Coal Mines (Sangamon County) - Mine names, mine index, ownership, years of operation.

Mine notes (Sangamon County) - Mine type, shaft locations, seam, depth, thickness, geologic problems.

Microfilm map, document 351231, reel 03134, frames 460-463 - Shaft locations, mine outline, mining method.

Mine Index 861**Bryan Eddy Coal Company, Eddy Mine**

Type: Underground Total mined-out acreage shown: 314

SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS

Type	County	Township-Range	Section	Quarters-Footage
Main shaft	Sangamon	17N 5W	16	SE SW NE NW
Air shaft	Sangamon	17N 5W	16	NE NE NW

GEOLOGY

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Ave	
Springfield	150			6.0	RPP

Geologic Problems Reported:

PRODUCTION HISTORY

Company	Mine Name	Years	Production (tons)
Louis F. Fisher Coal Company	Fisher	1920-1925	7,420
John Jacaway Coal Company	Jacaway	1925-1926	3,742
Fisher Coal Company	Fisher	1927-1933 *	750
McFall & Eddy	McFall & Eddy	1934-1934	862
Bryan Eddy Coal Company	Eddy	1935-1964	<u>1,393,436</u>
			1,406,210

* Idle 1929, and mines producing less than 1,000 tons per year were not reported from 1930 to 1933.

Last reported production: August 1964

SOURCES OF DATA

Source Map	Date	Original Scale	Digitized Scale	Map Type
Microfilm, document 351201	8-25-1964	1:2400	1:4634	Final

Annotated Bibliography (data source, brief description of information)

Coal Reports - Production, ownership, years of operation.

Directory of Illinois Coal Mines (Sangamon County) - Mine names, mine index, ownership, years of operation.

Mine notes (Sangamon County) - Mine type, shaft locations, seam, depth, thickness.

Microfilm map, document 351201, reel 03134, frames 367-368 - Shaft locations, mine outline, mining method.

Mine Index 925**R. & S. Coal Company, Cantrall Mine**

Type: Underground Total mined-out acreage shown: 107

SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS

Type	County	Township-Range	Section	Quarters-Footage
Main shaft	Sangamon	17N 5W	21	SW NW NW
Air shaft	Sangamon	17N 5W	21	NE SW NW

GEOLOGY

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Ave	
Springfield	217			6.0	RPP

Geologic Problems Reported:**PRODUCTION HISTORY**

Company	Mine Name	Years	Production (tons)
Cantrall Coal Company	Cantrall	1935-1962	550,042
R. & S. Coal Company	Cantrall	1963-1964	9,729
			559,771

Last reported production: February 1964

SOURCES OF DATA

Source Map	Date	Original Scale	Digitized Scale	Map Type
Microfilm, document 351245	3-6-1964	1:2400	1:3972	Final

Annotated Bibliography (data source, brief description of information)

Coal Reports - Production, ownership, years of operation.

Directory of Illinois Coal Mines (Sangamon County) - Mine names, mine index, ownership, years of operation.

Mine notes (Sangamon County) - Mine type, shaft location, seam, depth, thickness.

Microfilm map, document 351245, reel 03134, frame 495 - Shaft locations, mine outline, mining method.

Mine Index 2939**Athens-Dawson Fuel Company, Athens No. 1 Mine**

Type: Underground Total mined-out acreage shown: 330 Production indicates approximately 178 acres were mined after the map date.

SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS

Type	County	Township-Range	Section	Quarters-Footage
Main shaft	Menard	17N 5W	6	NW SW NW
Escape shaft	Menard	17N 5W	6	NW SW NW

GEOLOGY

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Ave	
Springfield	200			5.5-6.25	MRP

Geologic Problems Reported:

PRODUCTION HISTORY

Company	Mine Name	Years	Production (tons)
Athens Mining Company	Athens No. 2	1890-1907	1,473,063
Athens Mining Company	Athens No. 2	1907-1910	196,190 *
Athens Mining Company	Athens No. 2	1915-1916 **	126,986 *
Athens-Dawson Fuel Company	Athens No. 1	1916-1917	155,878 *
Athens-Dawson Coal Company	Athens No. 2	1917-1918	179,417 *
Athens-Dawson Coal Company	Athens No. 1	1918-1919	122,657 *
			2,254,191

* Production after map date

** Not operated from 1910 to 1915, reopened in fiscal year 1915-1916

Last reported production: June 1919

SOURCES OF DATA

Source Map	Date	Original Scale	Digitized Scale	Map Type
Microfilm, document 352214	2-4-1921	1:2400	1:4800	Secondary source
State archive, MSHA_1310	7-1907	1:2400	1:2400	Not final

Annotated Bibliography (data source, brief description of information)

Coal Reports - Production, ownership, years of operation, seam, thickness, depth, mining method.

Directory of Illinois Coal Mines (Menard County) - Mine names, mine index, ownership, years of operation.

Mine notes (Menard County) - Thickness, depth.

ISGS mined-out area map (Menard County) - Shaft location.

Microfilm map, document 352214, reel 03138, frames 271-272, map of Union Fuel No. 4 Mine (Mine Index 34) -

Mine outline (northwest).

Company map, state archive, MSHA_1310 - Shaft locations, mine outline, mining method.

Mine Index 2940
Perkins & Hughes, Perkins Mine

Type: Underground Total mined-out acreage shown: 9 Production indicates approximately 20 acres were mined after the map date.

SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS

Type	County	Township-Range	Section	Quarters-Footage
Main shaft	Menard	17N 6W	2	SW SE NE
Air shaft	Menard	17N 6W	2	2049 FNL, 1407 FEL

GEOLOGY

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Ave	
Springfield	154			6.0	MRP

Geologic Problems Reported:

PRODUCTION HISTORY

Company	Mine Name	Years	Production (tons)
Perkins & Hughes	Perkins & Hughes	1920-1927	26,904 *
Perkins & Hughes	Perkins & Hughes	1927-1929	15,432 **
H. A. Perkins	Perkins	1930-1930	7,200 **
Perkins & Hughes	Perkins & Hughes	1931-1931	7,012 **
Harry A. Perkins	Perkins	1932-1936	45,726 **
Perkins Coal Company	Perkins	1937-1938	7,777 **
Harry A. Perkins	Perkins	1939-1939	5,869 **
Perkins Coal Company	Perkins	1940-1941	11,925 **
Joe Hopkins & Elmer Stone	Perkins	1941-1942	3,826 **
			<u>131,671</u>

* Production was not reported in 1922 for mines producing less than 10,000 tons

** Production since map date

Last reported production: 1942

SOURCES OF DATA

Source Map	Date	Original Scale	Digitized Scale	Map Type
Microfilm, document 352217	4-1927	1:2400	1:2483	Not final

Annotated Bibliography (data source, brief description of information)

Coal Reports - Production, ownership, years of operation, seam, depth, thickness.

Directory of Illinois Coal Mines (Menard County) - Mine names, mine index, ownership, years of operation.

Mine notes (Menard County) - Mine type, shaft location.

Microfilm map, document 352217, reel 03138, frame 275 - Shaft locations, mine outline, mining method.

Mine Index 3358
Barr Coal Company, Barr Mine

Type: Underground Total mined-out acreage shown: 160 Production indicates an additional 7 acres were mined after the map date.

SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS

Type	County	Township-Range	Section	Quarters-Footage
Main shaft	Sangamon	17N 5W	6	193 FNL, 1177 FEL
Air shaft	Sangamon	17N 5W	6	501 FNL, 1235 FEL

GEOLOGY

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Ave	
Springfield	230			6.0	MRP

Geologic Problems Reported:

PRODUCTION HISTORY

Company	Mine Name	Years	Production (tons)
Barr Coal Company	Barr	1922-1951	662,172
Barr Coal Company	Barr	1952-1952	29,726 *
			691,898

* Production after map date

Last reported production: 1952

SOURCES OF DATA

Source Map	Date	Original Scale	Digitized Scale	Map Type
Microfilm, document 351254	5-19-1951	1:2400	1:4634	Not final

Annotated Bibliography (data source, brief description of information)

Coal Reports - Production, ownership, years of operation.

Directory of Illinois Coal Mines (Sangamon County) - Mine names, mine index, ownership, years of operation.

Mine notes (Sangamon County) - Mine type, shaft location, depth, thickness.

Microfilm, document 351254, reel 03134, frame 507 - Shaft locations, mine outline, mining method.

Mine Index 3359**Sangamon Valley Coal Company, Sangamon Valley Mine**

Type: Underground Total mined-out acreage shown: 8 Production indicates an additional 5 acres were mined after the map date.

SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS

Type	County	Township-Range	Section	Quarters-Footage
Main shaft	Sangamon	17N 5W	33	3660 FSL, 1050 FWL
Air shaft	Sangamon	17N 5W	33	NE SW NW

GEOLOGY

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Ave	
Springfield	138			6.0	RPB

Geologic Problems Reported:

PRODUCTION HISTORY

Company	Mine Name	Years	Production (tons)
Sangamon Valley Coal Company	Sangamon Valley	1939-1940	24,278
Fred Othen	Sangamon Valley	1941-1941	11,076
Sangamon Valley Coal Company	Sangamon Valley	1942-1945	18,432
Sangamon Valley Coal Company	Sangamon Valley	1945-1947	3,800 *
			57,586

* Production after map date

Last reported production: 1947

SOURCES OF DATA

Source Map	Date	Original Scale	Digitized Scale	Map Type
Microfilm, document 351188	11-4-1945	1:2400	1:3807	Not final

Annotated Bibliography (data source, brief description of information)

Coal Reports - Production, ownership, years of operation.

Directory of Illinois Coal Mines (Sangamon County) - Mine names, mine index, ownership, years of operation.

Mine notes (Sangamon County) - Mine type, shaft locations, seam, depth, thickness.

Microfilm map, document 351188, reel 03134, frame 347 - Shaft locations, mine outline, mining method.

MINES WHOSE LOCATIONS ARE NOT KNOWN, ATHENS QUADRANGLE

The locations of the following mines are unknown, but the production tonnage, operating names, and nearest town were reported in the Annual Coal Reports. The operators listed below mined in or near the Athens Quadrangle. The information shown is similar to that presented on the summary sheets in the previous pages of this directory. The first item is the name the mine operated under as listed in the Coal Report, then the years the mine reported. If no physical data are available, the next item listed is the total tons produced by the mine. If physical data are available, the order of presentation is as follows: type of opening for the mine (drift, slope or shaft), depth of coal in feet, and thickness of coal in feet.

The total tons mined by these unlocated mines is 312,687 (311,494 underground and 1,193 by unknown method), which would represent approximately 50 to 80 acres, depending on the recovery factor, mining method, and numerous other factors. (Note: 1 square mile = 640 acres)

Near Athens, in Menard County

Galaway & Company, 1881-1882, shaft, Springfield, 225-227, 6.0, RP	20,000 tons
Athens Coal Company, No. 1 Mine, 1882-1891	<u>288,694</u> tons
	308,694 tons
This mine was on the Wabash Railroad, about ½ mile west of No. 2 Mine (mine index 2939).	
Hall (Banks), 1881-1882, shaft, Springfield, 180, 6.0	1,600 tons
Brown (William), 1909-1911, shaft, Springfield, —, 5.5, RP	1,200 tons
Ferguson (Jess), 1926-1926	124 tons
Wilbanks Coal Company, 1940-1940	250 tons
Kent (Art), 1941-1941	759 tons
Bryant & Walter, 1942-1942	<u>60</u> tons
	1,069 tons

INDEX OF MINES IN THE ATHENS QUADRANGLE

Athens Coal Company, No. 1 Mine	18
Athens Mining Company	14
Athens-Dawson Coal Company, No. 1 Mine	14
Athens-Dawson Coal Company, No. 2 Mine	14
Athens-Dawson Fuel Company	14
Barr Coal Company	16
Brown (William)	18
Bryant & Walter	18
Buckley Coal Company	10
Cantrall Co-operative Coal Company	10
Cantrall Coal Company	10, 13
Cantrall Mine	10, 13
Cora Coal Company	11
Dawson (Athens-Dawson Coal Company, No. 1 Mine)	14
Dawson (Athens-Dawson Coal Company, No. 2 Mine)	14
Dawson (Athens-Dawson Fuel Company)	14
Eddy (Brian) Coal Company	12
Eddy (McFall & Eddy)	12
Ferguson (Jess)	18
Fisher (Louis F.) Coal Company	12
Fisher Coal Company	12
Galaway & Company	18
Hall (Banks)	18
Hopkins & Stone	15
Hughes (Perkins & Hughes)	15
Jacaway (John) Coal Company	12
Kent (Art)	18
McFall & Eddy	12
Othen (Fred)	17
Peabody Coal Company, No. 51 Mine	11
Perkins (Harry A.)	15
Perkins & Hughes	15
Perkins Coal Company	15
R. & S. Coal Company, Cantrall Mine	13
Sangamon Coal Company	10
Sangamon Valley Coal Company	17
Springfield District Coal Mining Company, No. 1 Mine	11
Springfield District Coal Mining Company, No. 51 Mine	11
Stone (Hopkins & Stone)	15
Union Fuel Coal Company, No. 4 Mine	9
Wabash Coal Company	9
Wabash Coal Company, No. 2 Mine	9
Walter (Bryant & Walter)	18
Wilbanks Coal Company	18

Funds to compile the map and directory of coal mines in the Athens Quadrangle were provided by the Illinois Abandoned Mined Lands Reclamation Council and the Illinois Mine Subsidence Insurance Fund.