















## SPRINGFIELD COAL

This map accompanies the Coal Mines Directory for the Bloomington West Quadrangle and maps of mines in the Colchester Coal, Bloomington West Quadrangle. Consult the directory for a complete explanation of the information shown on this map.

## MINING METHOD

-  Room & pillar (RP)
-  Room & pillar - basic (RPB)
-  Modified room & pillar (MRP)
-  Room & pillar panel (RPP)
-  Blind room & pillar (BRP)
-  Checkerboard room & pillar (CRP)
-  High extraction retreat (HER)
-  Longwall (LW)
-  Underground mine, method unknown
-  General area of mining
-  Surface mine

#### SOURCE OF MINE OUTLINES

-  Final mine map
-  Not a final map
-  Undated map
-  Incomplete map
-  Secondary source map

## TIPPLE, SHAFT, SLOPE, DRIFT LOCATIONS

- ☒ ☒ Strip mine tipples; active - abandoned
- ☒ ☒ Mine shaft; active - abandoned
- ☒ ☒ Mine slope; active - abandoned
- ☒ ☒ Mine drift; active - abandoned
- ☐ Air shaft
- ☐ Uncertain location
- ☐ Uncertain type of opening

## MINE ANNOTATION

(space permitting)

Company

**Mine Name**

ISGS Index No., Years of Operation

## LOCATION



## DISCLAIMER

These data were compiled and digitized from the best source maps available. Locations of some features may be offset by 500 feet or more due to errors in the original source maps, the compilation process, digitizing, or a combination of these factors. Documentation of the source materials used is contained in the directory that accompanies this map. It is the user's responsibility to read this documentation and understand the limitations of the data. Though efforts have been made to compile these data accurately, the Illinois State Geological Survey does not guarantee the validity or the accuracy of these data.


The image of the U.S.G.S. Bloomington West quadrangle used as a basemap was projected from the original UTM to Lambert Conformable Conic.



Illinois State Geological Survey  
615 E. Peabody Drive  
Champaign, IL 61820

Mine outlines compiled by Andrew G. Louchios












March 4, 2004






## COLCHESTER COAL

This map accompanies the Coal Mines Directory for the Bloomington West Quadrangle and maps of mines in the Springfield Coal, Bloomington West Quadrangle. Consult the directory for a complete explanation of the information shown on this map.

## MINING METHOD

-  Room & pillar (RP)
-  Room & pillar - basic (RPB)
-  Modified room & pillar (MRP)
-  Room & pillar panel (RPP)
-  Blind room & pillar (BRP)
-  Checkerboard room & pillar (CRP)
-  High extraction retreat (HER)
-  Longwall (LW)
-  Underground mine, method unknown
-  General area of mining
-  Surface mine

#### SOURCE OF MINE OUTLINES

-  Final mine map
-  Not a final map
-  Undated map
-  Incomplete map
-  Secondary source map

## TIPPLE, SHAFT, SLOPE, DRIFT LOCATIONS

- ☒ ☒ Strip mine tipples; active - abandoned
- ☒ ☒ Mine shaft; active - abandoned
- ☒ ☒ Mine slope; active - abandoned
- ☒ ☒ Mine drift; active - abandoned
- ☐ Air shaft
- ☐ Uncertain location
- ☐ Uncertain type of opening

## MINE ANNOTATION

(space permitting)

Company

**Mine Name**

ISGS Index No., Years of Operation

## LOCATION



## DISCLAIMER

These data were compiled and digitized from the best source maps available. Locations of some features may be offset by 500 feet or more due to errors in the original source maps, the compilation process, digitizing, or a combination of these factors. Documentation of the source materials used is contained in the directory that accompanies this map. It is the user's responsibility to read this documentation and understand the limitations of the data. Though efforts have been made to compile these data accurately, the Illinois State Geological Survey does not guarantee the validity or the accuracy of these data.


The image of the U.S.G.S. Bloomington West quadrangle used as a basemap was projected from the original UTM to Lambert Conformable Conic.



Illinois State Geological Survey  
615 E. Peabody Drive  
Champaign, IL 61820

Mine outlines compiled by Andrew G. Louchios  
and Cheri A. Chenoweth

March 14, 2004





# **DIRECTORY OF COAL MINES IN ILLINOIS 7.5-MINUTE QUADRANGLE SERIES BLOOMINGTON WEST QUADRANGLE MCLEAN COUNTY**

Cheri Chenoweth & Andrew Louchios



Department of Natural Resources  
ILLINOIS STATE GEOLOGICAL SURVEY  
2004



**DIRECTORY OF COAL MINES IN ILLINOIS  
7.5-MINUTE QUADRANGLE SERIES  
BLOOMINGTON WEST QUADRANGLE  
MCLEAN COUNTY**

2004

ILLINOIS STATE GEOLOGICAL SURVEY  
William Shilts, Chief

Natural Resources Building  
615 East Peabody Drive  
Champaign, Illinois 61820

Phone 1-217-244-2420  
Fax 1-217-333-2830

**Cover photo** Track-mounted duckbill loading machine at a Peabody Coal Company mine, ca. 1915.

DISCLAIMER: The accuracy and completeness of mine maps and directories vary with the availability of reliable information. Maps and other information used to compile this mine map and directory were obtained from a variety of sources and the accuracy of some of the original information cannot be verified. Consequently, the Illinois State Geological Survey (ISGS) cannot guarantee the mine maps are free of errors and disclaims any responsibility for damages that may result from actions or decisions based on them.

The ISGS updates the maps and directories periodically, and welcomes any new information or corrections. Please contact the Coal Section of the ISGS at the address shown on the title page of this directory, or telephone (217) 244-2420.

*Printed by authority of the State of Illinois/2004*

## CONTENTS

INTRODUCTION .....	1
MINING IN THE BLOOMINGTON WEST QUADRANGLE .....	1
PART I EXPLANATION OF MAP AND MINE SUMMARY SHEET .....	2
INTERPRETING THE MAP .....	2
Mine Type and Mining Method .....	2
SOURCE MAPS .....	3
POINTS AND LABELS .....	3
INTERPRETING A MINE SUMMARY SHEET .....	6
REFERENCES .....	8
PART II DIRECTORY OF MINES IN THE BLOOMINGTON WEST QUADRANGLE .....	9
MINE SUMMARY SHEETS .....	9
Mine Index 100	
McLean County Coal Company, McLean County No. 1 Mine .....	9
Mine Index 6373	
Illinois Coal Mining Company, Illinois Mine .....	10
INDEX OF MINES IN THE BLOOMINGTON WEST QUADRANGLE .....	11





## **INTRODUCTION**

Coal has been mined in 73 counties of Illinois. More than 4,500 coal mines have operated since commercial mining began in Illinois about 1810; fewer than 30 are currently active. To detail the extent and location of coal mining in Illinois, the Illinois State Geological Survey (ISGS) has compiled maps and directories of known coal mines. The ISGS offers maps at a scale of 1:100,000 and accompanying directories for each county in which coal mining is known to have occurred. Maps at a scale of 1:24,000 and accompanying directories such as this are available for selected quadrangles. Contact the ISGS for a list of these quadrangles.

These larger scale maps show the approximate positions of mines in relation to surface features such as roads and water bodies, and indicate the mining method used and the accuracy of the mine boundaries. The maps are useful for locating mine boundaries relative to specific properties and for assessing the potential for subsidence in an area. Mine boundaries compiled from final mine surveys are generally shown within 200 feet of their true position. As a result of poor cartographic quality and inaccuracies in the original mine surveys, boundaries of some older mines may be mislocated on the map by 500 feet or more. Original mine maps should be consulted in situations that require precise delineation of mine boundaries or internal workings of mined areas.

The directory serves as a key to the accompanying mine map and provides basic information on the coal mines. The directory is composed of two parts. Part I explains the symbols and patterns used on the accompanying map and the summary data presented for each mine. Part II numerically lists the mines in the quadrangle and summarizes the geology and production history of each mine.

## **MINING IN THE BLOOMINGTON WEST QUADRANGLE**

Coal was discovered in February 27, 1867 by the North Shaft Coal Company (Thomas Bunn, Judson Spaulding, Dr. H. C. Luce and James L. Ridelhuber), but the mine failed due to water problems. (This shaft was near the 1924 Bloomington water works.) In 1867, McLean County Coal Company sank a shaft in the location shown on the accompanying map and prospered. In the 1890s, shale removed from this mine contributed to the raw materials for the Bloomington Pressed Brick Company, and this brick was used for pavement and building. Bloomington is credited with having the first brick pavement in the United States, on the south and west side of the public square in 1877. However, most of the material used to make the bricks was brought from elsewhere, as the shale and underclay in the Bloomington area was not of the best quality for brick and tile purposes. Around the same time, the Bloomington Coal Company sunk a shaft near the tracks of the Chicago & St. Louis Railroad, located about a half mile north of the depot and about one mile north of the McLean County Coal Company. Years of operation and production for the Bloomington Coal Company mine are unknown.

A fourth mine in Bloomington was organized by miners striking the McLean County Coal Company in April of 1885. This mine (mine index 6373, Bloomington Co-operative Coal Company) operated for less than a year before abandoning the operation because of financial difficulties. It was re-opened in 1889, but operated for barely a year before selling and then closing again. The Coal Report repeated a suspicion that the mine was bought by the McLean County Coal Company, which left only one mine operating in Bloomington.

## PART I EXPLANATION OF MAP AND MINE SUMMARY SHEET

### INTERPRETING THE MAP

The map accompanying this directory shows the location of coal mines known to be present in the quadrangle. The map, corresponding to a U.S. Geological Survey (USGS) 7.5-minute quadrangle, covers an area bounded by lines of latitude and longitude 7.5-minutes apart. In Illinois, a quadrangle is approximately 6.5 miles east to west and 8.5 miles north to south, an area of about 56 square miles. The USGS generally offers one map of mines per quadrangle. In some areas, however, extensive mining occurred in two or more overlapping seams. Separate maps are compiled for mines in each seam to maintain the readability of the map for these areas.

#### Mine Type and Mining Method

The mine type is indicated on the map by pattern color: green represents surface mines; red and yellow represent underground mines. The red patterns are used for areas of underground mining that are documented by a primary or secondary source map. A yellow pattern is used for cases where no map of the mine workings is available, but a general area of mining can be inferred from property maps or production figures. The patterns indicate the main mining methods used in underground mines. The methods are (1) room and pillar and (2) high extraction. The method used gives some indication of the amount and pattern of coal extraction within each mined area, and has some influence on the timing and type of subsidence that can occur over a mine.

The following discussion and illustrations of mining methods are based on Guither et al. (1984).

In room-and-pillar mines, coal is removed from haulage-ways (entries) and selected areas called rooms. Pillars of unmined coal are left between the rooms to support the roof. Depending on the size of rooms and pillars, the amount of coal removed from the production areas will range from 40% to 70%.

**Room and Pillar** - mining is divided into six categories:

- room-and-pillar basic (RPB, fig. 1A), an early method that did not follow a preset mining plan and therefore resulted in very irregular designs;
- modified room and pillar (MRP, fig. 1B);
- room-and-pillar panel (RPP, fig. 1C);
- blind room and pillar (BRP, fig. 1D);
- checkerboard room and pillar (CRP, fig. 1E);
- room and pillar (RP), a classification used when the specific type of room-and-pillar mining is unknown.

Blind and checkerboard are the most common types of room-and-pillar mining used in Illinois today. The knowledge of room-and-pillar mining methods gives a trained engineer information on the nature of subsidence that may occur. A more extensive discussion of subsidence can be found in Bauer et al. (1993).

**High-extraction** These mining methods are subdivided into high-extraction retreat (HER, Fig 1F) and longwall (LW, Fig 1G, 1H). In these methods, much of the coal is removed within well defined areas of the mine. Subsidence of the surface above these areas occurs within weeks. Once the subsidence activity ceases, the potential for further movement over these areas is low; however, subsidence may continue for several years after mining.

High-extraction retreat mining is a form of room-and-pillar mining that extracts most of the coal. Rooms and pillars are developed in the panels, and the pillars are then systematically removed (fig. 1F).

In early (pre-1960) longwall mines, mining advanced in multiple directions from a central shaft (fig. 1G). Large pillars of coal were left around the shaft, but all coal was removed beyond these pillars. Miners placed rock and wooden props and cribs in the mined-out areas to support the mine roof. The overlying rock gradually settled onto these supports, thus producing subsidence at the surface. In post-1959 longwall mines, room-and-pillar methods have been used to develop the main entries of the mine and panel areas. Modern longwall methods extract 100 percent of the coal in the panel areas (fig. 1H).

## SOURCE MAPS

Mine outlines depicted on the map are, whenever possible, based on maps made from original mine surveys. The process of compiling and digitizing the quadrangle map may produce small errors of less than 200 feet in the location of mine boundaries. Larger errors of 500 feet or more are possible for mines that have incomplete or inaccurate source maps.

Because of the extreme complexity of some mine maps, detailed features of mined areas have been omitted. The digitized mine boundary includes the exterior boundary of all rooms or entries that were at least 80 feet wide or protruded 500 feet from the main mining area. Unmined areas between mines are shown if they are at least 80 feet wide; unmined blocks of coal within mines are shown if they are at least 400 feet on each side. Original source maps should be consulted when precise information on mine boundaries or interior features is needed.

The mine summary sheet lists the source maps used to determine each mine outline. The completeness of map sources is indicated on the map by a line symbol at the mine boundary. Source maps are organized in five categories.

**Final mine map** The mine outline was digitized from an original map made from mine surveys conducted within a few months after production ceased. The date of the map and the last reported production are listed on the summary sheet.

**Not a final map** The mine is currently active or the mine outline was made from a map based on mine surveys conducted more than a few months before production ceased. This implies the actual mined-out area is probably larger than the outline on the map. The mine summary sheet indicated the dates of source maps and the last reported production, as well as the approximate tonnage mined between these two dates (if the mine is abandoned). The summary sheet also lists the approximate acreage mined since the date of the map and, in some cases, indicates the area where additional mining may have taken place. This latter information is determined by locating on the map the active faces relative to probable boundaries of the mine property.

**Undated map** The source map was undated, so it may or may not be based on a final mine survey. When sufficient data are available, the probable acreage of the mined area is estimated from reported production, average seam thickness and a recovery rate comparable to other mines in the area. This information is listed in the summary sheet for the mine.

**Incomplete map** The source map did not show the entire mine. The summary sheet indicates the missing part of the mine map and the acreage of the unmapped area, which is estimated from the amount of coal known to have been produced from the mine.

**Secondary source map** The original mine map was not found so the outline shown was determined from secondary sources (e.g., outlines from small-scale regional maps published in other reports). The summary sheet describes the secondary sources.

## POINTS AND LABELS


The locations of all mine openings (shafts, slopes, and drifts) and surface mine tipples are plotted on the map. Tipples are areas where coal was cleaned, stockpiled, and loaded for shipping.

Only openings or tipples are plotted for mines without source maps. If the precise locations of these features are unknown, a special symbol is used to indicate the approximate location of the mine.

Each mine on the map is labeled with the names of the mine and operating company, ISGS mine index number, and years of operation (if known) if space permits. A seam designation is given on maps where more than one seam was mined. For a mine that operated under more than one name, only the most recent name is generally given. When a mine changed names or ownership shortly before closing, an earlier name is listed. All company and mine names are listed on the mine summary sheet in the directory, under the production history segment.

**Figure 1** Mining methods: (A) room-and-pillar basic (RPB), (B) modified room and pillar (MRP), (C) room-and-pillar panel (RPP), (D) blind room and pillar (BRP).

**Figure 1** (*cont.*) Mining methods: (E) checkerboard room and pillar (CRP), (F) high extraction retreat (HER), (G) early (pre-1960) longwall, (H) post-1959 longwall



**Figure 2** Generalized stratigraphic section, showing approximate vertical relations of coals in Illinois.

surveyed location and is not derived from maps. Entry points are also plotted on the map and coded for the type of entry or tippie. A mine opening may have had many purposes during the life of the mine. Old hoist shafts are often later used for air and escape shafts; this information is included in the directory when known. The tippie for underground mines was generally located near the main shaft or slope. At surface mines, coal was sometimes hauled to a central tippie several miles from the mine pit.

## GEOLOGY

**Seam(s) mined** The name of the coal seam(s) mined is listed if known. If multiple seams were mined, they are all listed, although the mined-out area for each seam may be shown on separate maps. Figure 2 shows the stratigraphic section for Illinois, and the vertical relations of coals.

**Depth** The depth to the top of the seam in the vicinity of the shaft is listed if known. The depth is determined from notes made by geologists who visited the mine during its operation or from drill hole data in ISGS files. Depth generally varies little over the extent of the mine; however, reported depths for an individual mine vary. Depth for surface-mined coals varies, and is usually represented as a range.

**Thickness** The approximate thickness of the mined seam is shown if known. Thickness is also determined from notes of geologists who visited the mine during its operation or from borehole data in ISGS files. Minimum, maximum, and average thicknesses are given when this information is available.

**Mining method** The principal mining method used at the mine (figs. 1A-H) is listed. See the mining methods section at the beginning of this directory for a discussion of this parameter.

## INTERPRETING A MINE SUMMARY SHEET

The mine summary sheets are arranged numerically by mine index number. Index numbers are shown on the map and in the mine listing. The mine summary sheet provides the following information (if available).

**Company and mine name** The last company or owner of the mine is used, unless no production was recorded for the last owner. In that case, the penultimate owner is listed. Mines often have no specific name; in these cases, the company name is also used as the mine name.

**Type** *Underground* denotes a subsurface mine in which the coal was reached through a shaft, slope, or a drift entry. *Surface* denotes a surface or strip mine.

**Total mined-out acreage shown** The total acreage of the mined area mapped, including any acreage mined on adjacent quadrangles, is calculated from the digitized outline of the mine. The acreage of large barrier pillars depicted on the map is excluded from the mined-out acreage. Small pillars not digitized are included in the acreage calculation. If the mine outline is not based on a final mine map, the acreage is followed by an estimate of additional acres that may have been mined. The estimate is determined from reported mine production, approximate thickness of the coal, and recovery rates calculated from nearby mines that used similar mining methods.

## SHAFT, SLOPE, DRIFT OR TIPPLE LOCATIONS

**Shaft, slope, drift, or tippie locations** Locations of all known former entry points to underground mines or the location of coal cleaning and shipping equipment used by surface mines (the tippie) are listed. The location is described in terms of county, township and range (Twp-Rge), section, and location within the section by quarters. NE SW NW, for instance, would describe the location in the northeast quarter of the southwest quarter of the northwest quarter. Approximate footage from the section lines (FEL = from east line, FNL = from north line, for example) is given when that information is known; this indicates a

**Geologic problems reported** Any geologic problems, such as faults, water seepage, floor heaving, and unstable roof, encountered in the mine are reported. This information is from notes made by ISGS geologists who visited the mine, or from reports by mine inspectors published by the Illinois Department of Mines and Minerals, or from the source map(s). Geologic problems are not reported for active mines.

## PRODUCTION HISTORY

**Production history** Tons of coal produced from the mine by each mine owner are totaled. When the source map used for the mine outline is not a final mine map, the tonnage produced since the date of the map is identified. For mines that extend into adjacent quadrangles, the tonnage reported includes areas mined in adjacent quadrangles.

## SOURCE OF DATA

**Source map** This section lists information about the map(s) used to compile the mine outline and the locations of tipples and mine openings. In some cases more than one source map was used. For example, a map drawn before the mine closed may provide better information on original areas of the mine than a later map. When more than one map was used, the bibliography section explains what information was taken from each source.

**Date** The date of the most recent mine survey listed on the source map is reported.

**Original scale** The original scale of the source map is listed. Many maps are photo-reductions and are no longer at their original scale. The original scale gives some indication of the level of detail of the mine outline and the accuracy of the mine boundary relative to surface features. Generally, the larger the scale, the greater the accuracy and detail of the mine map. Mine outlines taken from source maps at scales smaller than 1:24,000 may be highly generalized and are probably not accurately located with respect to surface features.

**Digitized scale** The scale of the digitized map is reported. The scale may be different from that of the original source map. In many cases the digitized map was made from a photo-reduction of the original source map, or the source map was not in a condition suitable for digitizing and the mine boundaries were transferred to another base map.

**Map type** Source maps are classified into five categories to indicate the probable completeness of the map. See discussion of source maps in the previous section.

**Annotated bibliography** Sources that provide information about the mine are listed, with the data taken from each source. Some commonly used sources are described below. Full bibliographic references are given for all other sources. Unless otherwise noted, all sources are available for public inspection at the ISGS.

**Coal Reports** Published since 1881, these reports contain tabular data on mine ownership, production, employment, and accidents. Some volumes include short descriptions made by mine inspectors of physical features and conditions in selected mines.

**Directory of Illinois Coal Mines** This source is a compilation of basic data about Illinois coal mines, originally gathered by ISGS staff in the early 1950s. Sources used for this directory are undocumented, but they are primarily Illinois Department of Mines and Minerals annual reports, ISGS mine notes, and coal company officials.

**ENR Document 85/01**, Guither, H. D., J. K. Hines, and R. A. Bauer, 1985 The Economic Effect of Underground Mining Upon Land Used for Illinois Agriculture: Illinois Department of Energy and Natural Resources Document 85/01, 185 p.

**Microfilm map** The U.S. Bureau of Mines maintains a microfilm archive of mine maps. A microfilm file for Illinois is available for public viewing at the ISGS.



*Mine notes* ISGS geologists have visited mines or contacted mine officials throughout the state since the early 1900s. Notes made during these visits range from brief descriptions of the mine location to long narratives (including sketches) of mining conditions and geology.

*Federal Land Bank of St. Louis, Preliminary Reports on Subsidence Investigations* Mining engineers working for the Federal Land Bank of St. Louis mapped areas of subsidence due to coal mining in the early 1930s. These reports often include county maps of mine properties with mined-out areas including shaft locations, as well as subsidence areas.

## REFERENCES

Bauer, R. A., B. A. Trent, and P. B. Dumontelle, 1993, Mine Subsidence in Illinois: Facts for the Homeowner Considering Insurance: Illinois State Geological Survey, Environmental Geology Note 144, 16p.

Guither, H. D., J. K. Hines, and R. A. Bauer, 1985, The Economic Effects of Underground Mining Upon Land Used for Illinois Agriculture: Illinois Department of Energy and Natural Resources Document 85/01, 185p.

Hasbrouck, J. L., 1924, History of McLean County, Historical Publishing Company, Topeka-Indianapolis, 688p.

## PART II DIRECTORY OF MINES IN THE BLOOMINGTON WEST QUADRANGLE

### MINE SUMMARY SHEETS

A summary sheet on the geology and production history of each mine in the Bloomington West Quadrangle is provided. The summary is arranged numerically by mine index number, which is shown on the map and in the mine listing. Consult Part I for a complete explanation of the data listed in the summary sheet.

#### Mine Index 100

#### McLean County Coal Company, McLean County No. 1 Mine

Type: Underground    Total mined-out acreage shown: 528 (Springfield Coal), 76 (Colchester Coal).  
Production indicates an additional 100 acres were mined after the map date.

#### SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS

Type	County	Township-Range	Section	Quarters-Footage
Main shaft	McLean	23N 2E	5	NE NW SE
Air/escape shaft (5 x 10)	McLean	23N 2E	5	NW NW SE
Old drop shaft *	McLean	23N 2E	5	SW NW NW
New drop shaft *	McLean	23N 2E	5	SE SW NW

\* These drop shafts connect the two seams, but did not extend to the surface. They are shown on the accompanying map as "uncertain type of opening" point symbols, and are shown only on the Colchester Coal map. The mine notes and Coal Reports both refer to these as slopes. All coal was hauled to the surface from the lower seam.

#### GEOLOGY

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Ave	
Springfield	400			4.0 (3.5-4.07)	LW
Colchester	513-545			3.67 (3.0-4.25)	LW

Geologic Problems Reported: The roof contained coal balls and slips (one death was caused by each of these circumstances). The roof of the Springfield Coal was 3 to 4 feet of black shale that seemed bonded to the coal with pyrite. Often 2 to 5 inches of coal were left with the roof. Horsebacks were very common in the Springfield Coal, occurring every 25 to 30 feet. The Springfield Coal contained thin streaks of plate-like pyrite that were difficult to remove from the coal. The Colchester Coal was very hard and pyrite concretions were common. As well, a continuous band of pyrite occurred 4 to 8 inches above the bottom of the seam, along with numerous vertical plates of pyrite and calcite. The floor heaved somewhat.

#### PRODUCTION HISTORY

Company	Mine Name	Years	Production (tons)
McLean County Coal Company	McLean No. 1	1867-1913	3,726,738 **
McLean County Coal Company	McLean No. 1	1913-1927	598,601 ***
			4,325,339

\*\* Production prior to 1882 is unknown.

\*\*\* Production after map date

Last reported production: 1927

#### SOURCES OF DATA

Source Map	Date	Original Scale	Digitized Scale	Map Type
Microfilm, document 353312	7-22-1913	1:2400	1:4800	Not final
Microfilm, document 353313	7-22-1913	1:2400	1:3475	Not final

#### Annotated Bibliography (data source, brief description of information)

Coal Reports - Production, ownership, years of operation, seam, depth, thickness, geologic problems.

Directory of Illinois Coal Mines (McLean County) - Mine names, mine index, ownership, years of operation.

ENR Document 85/01 - Mining method.

Mine notes (McLean County) - Mine type, shaft location, geologic problems.

Microfilm map, document 353312, reel 03142, frames 287-288 - Shaft locations, mine outline, mining method.

Microfilm map, document 353313, reel 03142, frame 289 - Shaft locations, mine outline, mining method.

**Mine Index 6373**  
**Illinois Coal Mining Company, Illinois Mine**

Type: Underground    Total mined-out acreage shown: None; production indicates approximately 12 acres were mined.

**SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS**

Type	County	Township-Range	Section	Quarters-Footage
Main shaft	McLean	23N 2E	6	NW SE *

\* The location is deduced from various text descriptions, and is designated on the accompanying map by an uncertain location point symbol. The descriptions from the Coal Reports were: "one mile west of town", "one mile west of Union Depot in Bloomington", "halfway between the Chicago & Alton and the Big Four Railroads."

**GEOLOGY**

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Ave	
Springfield	287-289			3.67	LW
Colchester	372-400			4.0	LW

Geologic Problems Reported: While sinking the shaft, 10 feet of water-saturated sand was encountered 50 feet below the surface. The sand dipped and was difficult to get through. The upper seam had a poor roof and was of lower quality coal than the lower seam, which was developed when the mine was re-opened in 1897. The lower seam (Colchester Coal) had a good black shale roof.

**PRODUCTION HISTORY**

Company	Mine Name	Years	Production (tons)
Bloomington Co-operative Coal Company	Bloomington	1885-1887	17,300
Illinois Coal Mining Company	Illinois	1898-1899 **	<u>25,000</u>
			42,300

\*\* The mine had been abandoned in 1887 because of inadequate financial resources to invest in the machinery needed to make the mine efficient. The shaft was deepened to the Colchester Coal in 1898 and both seams were mined. The mine was economically viable, and suspicions were voiced in the 1899 Coal Report that the McLean County Coal Company bought the mine to shut it down in order to remove competition.

Last reported production: 1899

**SOURCES OF DATA**

Source Map	Date	Original Scale	Digitized Scale	Map Type
Coal Reports	1885, 1898	(text only)	1:24000 ***	Secondary source

\*\*\* Point plotted onto 1:24,000 USGS quadrangle and digitized.

Annotated Bibliography (data source, brief description of information)

Coal Reports - Production, ownership, years of operation, seam, depth, thickness, mining method, geologic problems, shaft location.

Directory of Illinois Coal Mines (McLean County) - Mine names, mine index, ownership, years of operation.

Mine notes (McLean County) - Mine type, shaft location, geologic problems.

## INDEX OF MINES IN THE BLOOMINGTON WEST QUADRANGLE

Bloomington Co-operative Coal Company .....	10
Bloomington Coal Company .....	1
Illinois Coal Mining Company .....	10
McLean County Coal Company .....	9



Funding for this project was supplied by the Illinois Department of Natural Resources, Office of Mines and Minerals.