

DIRECTORY OF COAL MINES IN ILLINOIS

7.5-MINUTE QUADRANGLE SERIES

DEPUE QUADRANGLE

BUREAU & PUTNAM COUNTIES

Jennifer M. Obrad & C. Chenoweth



2009

Institute of Natural Resource Sustainability
William W. Shilts, Executive Director
ILLINOIS STATE GEOLOGICAL SURVEY
E. Donald McKay III, Interim Director

Natural Resources Building
615 East Peabody Drive
Champaign, Illinois 61820

Phone 217-244-4610
Fax 217-333-2830



This material is based upon work supported by the Illinois Mine Subsidence Insurance Fund. Any opinions, findings, and conclusions or recommendations expressed in this publication are those of the authors and do not necessarily reflect the views of the Illinois Mine Subsidence Insurance Fund.

Cover photo Track-mounted duckbill loading machine at a Peabody Coal Company mine, ca. 1915.

DISCLAIMER: The accuracy and completeness of mine maps and directories vary with the availability of reliable information. Maps and other information used to compile this mine map and directory were obtained from a variety of sources and the accuracy of some of the original information cannot be verified. Consequently, the Illinois State Geological Survey (ISGS) cannot guarantee the mine maps are free of errors and disclaims any responsibility for damages that may result from actions or decisions based on them.

The ISGS updates the maps and directories periodically, and welcomes any new information or corrections. Please contact the Coal Section of the ISGS at the address shown on the title page of this directory, or telephone (217) 244-4610.

© 2009 The Board of Trustees of the University of Illinois. All rights reserved.
For permission information, contact the Illinois State Geological Survey.

CONTENTS

INTRODUCTION	1
MINING IN THE DEPUE QUADRANGLE	1
PART I EXPLANATION OF MAP AND MINE SUMMARY SHEET	2
INTERPRETING THE MAP	2
Mine Type and Mining Method	2
Source Maps	3
Points and Labels	3
INTERPRETING A MINE SUMMARY SHEET	6
REFERENCES	8
PART II DIRECTORY OF MINES IN THE DEPUE QUADRANGLE	9
MINE SUMMARY SHEETS	9
Mine Index 8	
Marquette Third Vein Coal Company, Marquette Mine	9
Mine Index 241	
Spring Valley Coal Company, Spring Valley No. 4 Mine	10
Mine Index 244	
Coal Hollow Coal Company, Coal Hollow Mine	11
Mine Index 298	
Prairie State Coal Company, Prairie State Mine	12
Mine Index 6341	13
OTHER MINES SHOWN ON DEPUE QUADRANGLE	14
Mine Index 6342	14
INDEX OF MINES IN THE DEPUE QUADRANGLE	15

INTRODUCTION

Coal has been mined in 76 counties of Illinois. More than 7,400 coal mines have operated since commercial mining began in Illinois about 1810; fewer than 30 are currently active. To detail the extent and location of coal mining in Illinois, the Illinois State Geological Survey (ISGS) has compiled maps and directories of known coal mines. The ISGS offers maps at a scale of 1:100,000 and accompanying directories for each county in which coal mining is known to have occurred. Maps at a scale of 1:24,000 and accompanying directories, such as this, are available for selected quadrangles. Contact the ISGS for a list of these quadrangles.

These larger scale maps show the approximate positions of mines in relation to surface features such as roads and water bodies, and indicate the mining method used and the accuracy of the mine boundaries. The maps are useful for locating mine boundaries relative to specific properties and for assessing the potential for subsidence in an area. Mine boundaries compiled from final mine surveys are generally shown within 200 feet of their true position. As a result of poor cartographic quality and inaccuracies in the original mine surveys, boundaries of some older mines may be mislocated on the map by 500 feet or more. Original mine maps should be consulted in situations that require precise delineation of mine boundaries or internal workings of mined areas.

This directory serves as a key to the accompanying mine map and provides basic information on the coal mines in the quadrangle. The directory is composed of two parts. Part I explains the symbols and patterns used on the accompanying map and the summary data presented for each mine. Part II numerically lists the mines in the quadrangle and summarizes the geology and production history of each mine. Total production for the mine, not the portion in the quadrangle, is given.

MINING IN THE DEPUE QUADRANGLE

In the northwestern portion of the Depue Quadrangle, the Herrin Coal was mined with the room-and-pillar method. Clay slips were common in this seam, and the blue band was 3 inches thick in the Coal Hollow Mine (mine index 244). The earliest mining in this area took place in the Herrin Coal, along East Bureau Creek near Coal Hollow. The extent of mining is not known, but 7 mines were shown on the 1876 Atlas of Illinois.

In the eastern half of the quadrangle, longwall mining took place in the Colchester Coal. The roof was poor in the Marquette Mine (mine index 8), so that the weight of the roof compressed the gob stacked behind the active face, and subsidence breaks to the surface were noted. Pyrite was present in a clay parting and as nodules and lenses. The Spring Valley No. 4 Mine (mine index 241) had a thick underclay floor that was more than 14 feet thick.

PART I EXPLANATION OF MAP AND MINE SUMMARY SHEET

INTERPRETING THE MAP

The map accompanying this directory shows the location of coal mines known to be present in the quadrangle. The map, corresponding to a U.S. Geological Survey (USGS) 7.5-minute quadrangle, covers an area bounded by lines of latitude and longitude 7.5-minutes apart. In Illinois, a quadrangle is approximately 6.5 miles east to west and 8.5 miles north to south, an area of about 56 square miles. The USGS generally offers one map of mines per quadrangle. In some areas where extensive mining occurred in two or more overlapping seams, separate maps are compiled for mines in each seam to maintain readability of the map.

Mine Type and Mining Method

The mine type is indicated on the map by pattern color: green represents surface mines; red and yellow represent underground mines. The red patterns are used for areas of underground mining that are documented by a primary or secondary source map. A yellow pattern is used for cases where no map of the mine workings is available, but a general area of mining can be inferred from property maps or production figures. The patterns indicate the main mining methods used in underground mines. The methods are (1) room and pillar and (2) high extraction. The method used gives some indication of the amount and pattern of coal extraction within each mined area, and has some influence on the timing and type of subsidence that can occur over a mine.

The following discussion and illustrations of mining methods are based on Guither et al. (1984).

In room-and-pillar mines, coal is removed from haulage-ways (entries) and selected areas called rooms. Pillars of unmined coal are left between the rooms to support the roof. Depending on the size of rooms and pillars, the amount of coal removed from the production areas will range from 40% to 70%.

Room and Pillar - mining is divided into six categories:

- room-and-pillar basic (RPB, fig. 1A), an early method that did not follow a preset mining plan and therefore resulted in very irregular designs;
- modified room and pillar (MRP, fig. 1B);
- room-and-pillar panel (RPP, fig. 1C);
- blind room and pillar (BRP, fig. 1D);
- checkerboard room and pillar (CRP, fig. 1E);
- room and pillar (RP), a classification used when the specific type of room-and-pillar mining is unknown.

Blind and checkerboard are the most common types of room-and-pillar mining used in Illinois today. The knowledge of room-and-pillar mining methods gives a trained engineer information on the nature of subsidence that may occur. A more extensive discussion of subsidence can be found in Bauer et al. (1993).

High-extraction These mining methods are subdivided into high-extraction retreat (HER, Fig 1F) and longwall (LW, Fig 1G, 1H). In these methods, much of the coal is removed within well defined areas of the mine. Subsidence of the surface above these areas occurs within weeks. Once the subsidence activity ceases, the potential for further movement over these areas is low; however, subsidence may continue for several years after mining.

High-extraction retreat mining is a form of room-and-pillar mining that extracts most of the coal. Rooms and pillars are developed in the panels, and the pillars are then systematically removed (fig. 1F).

In early (pre-1960) longwall mines, mining advanced in multiple directions from a central shaft (fig. 1G). Large pillars of coal were left around the shaft, but all coal was removed beyond these pillars. Miners placed rock and wooden props and cribs in the mined-out areas to support the mine roof. The overlying rock gradually settled onto these supports, thus producing subsidence at the surface. In post-1959 longwall mines, room-and-pillar methods have been used to develop the main entries of the mine and panel areas. Modern longwall methods extract 100 percent of the coal in the panel areas (fig. 1H).

SOURCE MAPS

Mine outlines depicted on the map are, whenever possible, based on maps made from original mine surveys. The process of compiling and digitizing the quadrangle map may produce errors of less than 200 feet in the location of mine boundaries. Larger errors of 500 feet or more are possible for mines that have incomplete or inaccurate source maps.

Because of the extreme complexity of some mine maps, detailed features of mined areas have been omitted. The digitized mine boundary includes the exterior boundary of all rooms or entries that were at least 80 feet wide or protruded 500 feet from the main mining area. Unmined areas between mines are shown if they are at least 80 feet wide; unmined blocks of coal within mines are shown if they are at least 400 feet on each side. Original source maps should be consulted when precise information on mine boundaries or interior features is needed.

The mine summary sheet lists the source maps used to determine each mine outline. The completeness of map sources is indicated on the map by a line symbol at the mine boundary. Source maps are organized in five categories.

Final mine map The mine outline was digitized from an original map made from mine surveys conducted within a few months after production ceased. The date of the map and the last reported production are listed on the summary sheet.

Not a final map The mine is currently active or the mine outline was made from a map based on mine surveys conducted more than a few months before production ceased. This implies the actual mined-out area is probably larger than the outline on the map. The mine summary sheet indicated the dates of source maps and the last reported production, as well as the approximate tonnage mined between these two dates (if the mine is abandoned). The summary sheet also lists the approximate acreage mined since the date of the map and, in some cases, indicates the area where additional mining may have taken place. This latter information is determined by locating on the map the active faces relative to probable boundaries of the mine property.

Undated map The source map was undated, so it may or may not be based on a final mine survey. When sufficient data are available, the probable acreage of the mined area is estimated from reported production, average seam thickness and a recovery rate comparable to other mines in the area. This information is listed in the summary sheet for the mine.

Incomplete map The source map did not show the entire mine. The summary sheet indicates the missing part of the mine map and the acreage of the unmapped area, which is estimated from the amount of coal known to have been produced from the mine.

Secondary source map The original mine map was not found so the outline shown was determined from secondary sources (e.g., outlines from small-scale regional maps published in other reports). The summary sheet describes the secondary sources.

POINTS AND LABELS

The locations of all known mine openings (shafts, slopes, and drifts) and surface mine tipples are plotted on the map. Tipples are areas where coal was cleaned, stockpiled, and loaded for shipping.

Only openings or tipples are plotted for mines without source maps. If the precise locations of these features are unknown, a special symbol is used to indicate the approximate location of the mine.

Each mine on the map is labeled with the names of the mine and operating company, ISGS mine index number, and years of operation (if known) if space permits. A seam designation is given on maps where more than one seam was mined. For a mine that operated under more than one name, only the most recent name is generally given. When a mine changed names or ownership shortly before closing, an earlier name is listed. All company and mine names are listed on the mine summary sheet in the directory, under the production history segment.



Figure 1 Mining methods: (A) room-and-pillar basic (RPB), (B) modified room and pillar (MRP), (C) room-and-pillar panel (RPP), (D) blind room and pillar (BRP).



Figure 1 (cont.) Mining methods: (E) checkerboard room and pillar (CRP), (F) high extraction retreat (HER), (G) early (pre-1960) longwall, (H) post-1959 longwall



Figure 2 Generalized stratigraphic section, showing approximate vertical relations of coals in Illinois.

INTERPRETING A MINE SUMMARY SHEET

The mine summary sheet is arranged numerically by mine index number. Index numbers are shown on the map and in the mine listing. The mine summary sheet provides the following information (if available).

Company and mine name The last company or owner of the mine is used, unless no production was recorded for the last owner. In that case, the penultimate owner is listed. Mines often have no specific name; in these cases, the company name is also used as the mine name.

Type *Underground* denotes a subsurface mine in which the coal was reached through a shaft, slope, or a drift entry. *Surface* denotes a surface, open pit or strip mine.

Total mined-out acreage shown The total acreage of the mined area mapped, including any acreage mined on adjacent quadrangles, is calculated from the digitized outline of the mine. The acreage of large barrier pillars depicted on the map is excluded from the mined-out acreage. Small pillars not digitized are included in the acreage calculation. If the mine outline is not based on a final mine map, the acreage is followed by an estimate of additional acres that may have been mined. The estimate is determined from reported mine production, approximate thickness of the coal, and recovery rates calculated from nearby mines that used similar mining methods.

SHAFT, SLOPE, DRIFT OR TIPPLE LOCATIONS

Shaft, slope, drift, or tippie locations Locations of all known former entry points to underground mines or the location of coal cleaning, tippie, and shipping equipment used by the mine's facility are listed. The location is described in terms of county, township and range (Twp-Rge), section, and location within the section by quarters. NE SW NW, for instance, would describe the location in the northeast quarter of the southwest quarter of the northwest quarter. When sections are irregular in size, the quarters remain the same size and are oriented (or "registered") from the southeast corner of the section. Approximate footage from the section lines (FEL = from east line, FNL = from north line, for example) is given when that information is known; this indicates a surveyed location and is not derived from maps. Entry points are also plotted on the map and coded for the type of entry or tippie. A mine opening may have had many purposes during the life of the mine. Old hoist shafts are often later used for air and escape shafts; this information is included in the directory when known. The tippie for underground mines was generally located near the main shaft or slope. At surface mines, coal was sometimes hauled to a central tippie several miles from the mine pit.

GEOLOGY

Seam(s) mined The name of the coal seam(s) mined is listed, if known. If multiple seams were mined, they are all listed, although the mined-out area for each seam may be shown on separate maps. Figure 2 shows the stratigraphic section of the coal-bearing interval in Illinois, and the vertical relations among the coals.

Depth The depth to the top of the seam in the vicinity of the shaft is listed, if known. The depth is determined from notes made by geologists who visited the mine during its operation or from drill hole data in ISGS files. Depth generally varies little over the extent of a mine; however, reported depths for an individual mine may vary. Depth for surface-mined coals varies, and is usually represented as a range.

Thickness The approximate thickness of the mined seam is shown, if known. Thickness also comes from notes of geologists who visited the mine during its operation or from borehole data in ISGS files. Minimum, maximum, and average thicknesses are given when this information is available.

Mining method The principal mining method used at the mine (figs. 1A-H) is listed. See the mining methods section at the beginning of this directory for a discussion of this parameter.

Geologic problems reported Any known geologic problems, such as faults, water seepage, floor heaving, and unstable roof, encountered in the mine are reported. This information is from notes made by ISGS geologists who visited the mine, or from reports by mine inspectors published by the Illinois Department of Mines and Minerals, or from the source map(s). Geologic problems are not reported for active mines.

PRODUCTION HISTORY

Production history Tons of coal produced from the mine by each mine owner are totaled. When the source map used for the mine outline is not a final mine map, the tonnage produced since the date of the map is identified. For mines that extend into adjacent quadrangles, the tonnage reported includes areas mined in adjacent quadrangles.

SOURCE OF DATA

Source map This section lists information about the map(s) used to compile the mine outline and the locations of tipples and mine openings. In some cases more than one source map was used. For example, a map drawn before the mine closed may provide better information on original areas of the mine than a later map. When more than one map was used, the bibliography section explains what information was taken from each source.

Date The date of the most recent mine survey listed on the source map is reported.

Original scale The original scale of the source map is listed. Many maps are photo-reductions and are no longer at their original scale. The original scale gives some indication of the level of detail of the mine outline and the accuracy of the mine boundary relative to surface features. Generally, the larger the scale, the greater the accuracy and detail of the mine map. Mine outlines taken from source maps at scales smaller than 1:24,000 may be highly generalized and may well be inaccurately located with respect to surface features.

Digitized scale The scale of the digitized map is reported. The scale may be different from that of the original source map. In many cases the digitized map was made from a photo-reduction of the original source map, or the source map was not in a condition suitable for digitizing and the mine boundaries were transferred to another base map.

Map type Source maps are classified into five categories to indicate the probable completeness of the map. See discussion of source maps in the previous section.

Annotated bibliography Sources that provide information about the mine are listed, with the data taken from each source. Some commonly used sources are described below. Full bibliographic references are given for all other sources. Unless otherwise noted, all sources are available for public inspection at the ISGS.

Coal Reports Published since 1881, these reports contain tabular data on mine ownership, production, employment, and accidents. Some volumes include short descriptions made by mine inspectors of physical features and conditions in selected mines.

Directory of Illinois Coal Mines This source is a compilation of basic data about Illinois coal mines, originally gathered by ISGS staff in the early 1950s. Sources used for this directory are undocumented, but they are primarily Illinois Department of Mines and Minerals annual reports, ISGS mine notes, and coal company officials.

ENR Document 85/01, Guither, H. D., J. K. Hines, and R. A. Bauer, 1985 The Economic Effect of Underground Mining Upon Land Used for Illinois Agriculture: Illinois Department of Energy and Natural Resources Document 85/01, 185 p.

Microfilm map The U.S. Bureau of Mines maintains a microfilm archive of mine maps. A microfilm file for Illinois is available for public viewing at the ISGS.

Mine notes ISGS geologists have visited mines or contacted mine officials throughout the state since the early 1900s. Notes made during these visits range from brief descriptions of the mine location to long narratives (including sketches) of mining conditions and geology.

Federal Land Bank of St. Louis, Preliminary Reports on Subsidence Investigations Mining engineers working for the Federal Land Bank of St. Louis mapped areas of subsidence due to coal mining in the early 1930s. These reports often include county maps of mine properties with mined-out areas including shaft locations, as well as subsidence areas.

REFERENCES

Bauer, R. A., B. A. Trent, and P. B. Dumontelle, 1993, Mine Subsidence in Illinois: Facts for the Homeowner Considering Insurance, Illinois State Geological Survey, Environmental Geology Note 144, 16p.

Guither, H. D., J. K. Hines, and R. A. Bauer, 1985, The Economic Effects of Underground Mining Upon Land Used for Illinois Agriculture, Illinois Department of Energy and Natural Resources Document 85/01, 185p.

PART II DIRECTORY OF MINES IN THE DEPUE QUADRANGLE

MINE SUMMARY SHEETS

A summary sheet on the geology and production history of each mine in the Depue Quadrangle is provided. These summary sheets are arranged numerically by mine index number. Consult Part I for a complete explanation of the data listed in the summary sheet.

Mine Index 8

Marquette Third Vein Coal Company, Marquette Mine

Type: Underground Total mined-out acreage shown: 561

SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS

Type	County	Township-Range	Section	Quarters-Footage
Main shaft	Bureau	16N 11E	31	SW NW SE

GEOLOGY

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Avg	
Colchester	280	3.0	3.67	3.5	LW

Geologic Problems Reported: The immediate roof was 5 to 10 feet of gray shale soapstone with a black shale above. The mine notes contain the statement that the roof was not very good, and "the roof settles heavily so that the gob is pressed solid". Breaks leading to surface subsidence were usually at an angle of 74 degrees up to the vertical. Occasional slips and rolls were small and infrequent. The coal had a clay parting ½ to 1 inch thick that included pyrite streaks. Pyrite was also present as lenses and balls in other parts of the seam. The underclay averaged 8 inches thick, but ranged up to 2 feet thick.

PRODUCTION HISTORY

Company	Mine Name	Years	Production (tons)
George H. Locey	Locey	pre1881-1887 *	193,366 *
A. O. Marshall (receiver)	Locey	1887-1889	82,497
Chicago, Wilmington & Vermilion Coal Co.	Loceyville	1889-1894	292,960
Marquette Third Vein Coal Company	Marquette	1894-1914	3,102,532
			3,671,355

* Production and years of operation before 1881 are not known. The 1882 Coal Report indicated 10 acres were mined.

Last reported production: March 1914

SOURCES OF DATA

Source Map	Date	Original Scale	Digitized Scale	Map Type
ISGS map library, 4103.B8 i5.1-5, sht. 5	1935	1:31680	1:31680	Secondary source

Annotated Bibliography (data source, brief description of information)

Coal Reports - Production, ownership, years of operation, seam.

Directory of Illinois Coal Mines (Bureau County) - Mine names, mine index, ownership, years of operation.

Mine notes (Bureau County) - Mine type, shaft location, depth, thickness, mining method, geologic problems.

ISGS map library, 4103.B8 i5.1-5, sheet 5, work map of Federal Land Bank Report - Shaft location, mine outline.

Mine Index 241
Spring Valley Coal Company, Spring Valley No. 4 Mine

Type: Underground Total mined-out acreage shown: 693

SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS

Type	County	Township-Range	Section	Quarters-Footage
Main shaft	Bureau	16N 11E	18	SW SE SW

GEOLOGY

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Avg	
Colchester	392	3.0	4.0	3.5	LW

Geologic Problems Reported: The roof over most of the mine was soapstone. The roof over remaining parts of the mine was black shale. Some rolls were noted. The underclay was at least 14 feet thick, much thicker than at other mines nearby.

PRODUCTION HISTORY

Company	Mine Name	Years	Production (tons)
Seaton Brothers	Seaton	1881-1888	14,564
Chicago, Wilmington & Vermilion Coal Co.	Seatonville	1888-1902	1,735,027
Spring Valley Coal Company	Spring Valley No. 4	1902-1913	2,208,398
			3,957,989

Last reported production: August 1913

SOURCES OF DATA

Source Map	Date	Original Scale	Digitized Scale	Map Type
ISGS map library, 4103.B8 i5.1-5, sht. 5	1935	1:31680	1:31680	Secondary source

Annotated Bibliography (data source, brief description of information)

Coal Reports - Production, ownership, years of operation, mining method.
 Directory of Illinois Coal Mines (Bureau County) - Mine names, mine index, ownership, years of operation.
 Mine notes (Bureau County) - Mine type, shaft location, depth, thickness, geologic problems.
 ISGS map library, 4103.B8 i5.1-5, sheet 5, work map of Federal Land Bank Report - Shaft location, mine outline.

Mine Index 244**Coal Hollow Coal Company, Coal Hollow Mine**

Type: Underground Total mined-out acreage shown: 12

SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS

Type	County	Township-Range	Section	Quarters-Footage
Main shaft	Bureau	16N 10E	17	NE SE SE

GEOLOGY

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Avg	
Herrin	180	2.0	5.0	4.5	RP

Geologic Problems Reported: The roof consisted of gray shale, black shale and some white top. Clay slips were common. The blue band averaged 3 inches thick at this mine, and consisted of gray to blue shale.

PRODUCTION HISTORY

Company	Mine Name	Years	Production (tons)
Bierman	Bierman	1870-1881 *, **	none reported **
Joseph Vane	Vane	1881-1883 **	2,361 **
George Heathcock	Heathcock	1883-1895	31,142
Bloom & Cox	Heathcock	1895-1897	5,607
George Heathcock	Heathcock	1897-1905	15,352
John Griffith & Son	Heathcock	1905-1906	1,406
Earl Saunders	Heathcock	1906-1907	780
Eugene Martin	Heathcock	1907-1908	1,310
John Griffith	Heathcock	1908-1910	2,648
Coal Hollow Coal Company	Coal Hollow	1910-1928 ***	6,462
			67,068

* Years of operation of Bierman's shaft uncertain; operating before the 1873 Geology and Paleontology of Illinois, Vol V (commonly known as the Worthen Reports).

** Production and the years of operation before 1881 are not known. The 1882 and 1883 Coal Reports indicated between 3 and 5 acres were mined.

*** Idle or abandoned 1910-1926. Coal Hollow Coal Company reopened the mine in 1926 and pulled pillars.

Last reported production: 1928

SOURCES OF DATA

Source Map	Date	Original Scale	Digitized Scale	Map Type
Federal Land Bank Report	6-1935	1:126720	1:126720	Secondary source

Annotated Bibliography (data source, brief description of information)

Coal Reports - Production, ownership, years of operation.

Directory of Illinois Coal Mines (Bureau County) - Mine names, mine index, ownership, years of operation.

Mine notes (Bureau County) - Mine type, shaft location, seam, depth, thickness, mining method, geologic problems.

Federal Land Bank Report (Perry County) - Shaft location, mine outline, mining method.

Worthen, A. H. & James Shaw, 1873, Geology and Paleontology, Geological Survey of Illinois, published by the authority of the Legislature of Illinois - Years of operation.

Mine Index 298**Prairie State Coal Company, Prairie State Mine**

Type: Underground Total mined-out acreage shown: 1,288 Production indicates approximately 30 acres were mined after the map date.

SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS

Type	County	Township-Range	Section	Quarters-Footage
Main shaft (8 x 16 ft)	Putnam	32N 1W	8	SE NW NE
Air shaft	Putnam	32N 1W	8	SW NE NE

GEOLOGY

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Avg	
Colchester	454			3.33	LW

Geologic Problems Reported: The roof was "mudstone". The coal dipped a considerable amount in local areas. The floor was clay and sandstone.

PRODUCTION HISTORY

Company	Mine Name	Years	Production (tons)
St. Paul Coal Company	St. Paul No. 1	1904-1929 *	6,319,056
Prairie State Coal Company	Prairie State	1930-1935	334,456
Prairie State Coal Company	Prairie State	1935-1938	153,026 **
			6,806,538

* Idle or abandoned 1925 to 1929

** Production after map date

Last reported production: 1938

SOURCES OF DATA

Source Map	Date	Original Scale	Digitized Scale	Map Type
Company, 4103.P82 i5.1-1	1-1924	1:2400	1:2400	Not final
Microfilm, document 352071	11-1935	1:2400	1:4800	Not final

Annotated Bibliography (data source, brief description of information)

Coal Reports - Production, ownership, years of operation.

Directory of Illinois Coal Mines (Putnam County) - Mine names, mine index, ownership, years of operation.

Mine notes (Putnam County) - Mine type, shaft location, shaft size, seam, depth, thickness, geologic problems.

Company map, ISGS map library, 4103.P82 i5.1-1 - Mine outline, shaft locations, mining method.

Microfilm map, document 352071, reel 03138, frame 43 - Mine outline (eastern side), mining method.

Mine Index 6341

Type: Underground Total mined-out acreage shown: None; a general area of mining has been drawn to encompass the area that may be affected by these very old mines.

SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS

Type	County	Township-Range	Section	Quarters-Footage
Mine	Bureau	16N 10E	17	NW NW SE
Mine	Bureau	16N 10E	17	SW NE SW
Mine	Bureau	16N 10E	17	NE SE SW
Mine	Bureau	16N 10E	17	SE SW SE
Mine	Bureau	16N 10E	20	SW NW NE
Mine	Bureau	16N 10E	20	SE NE NW
Mine	Bureau	16N 10E	20	NW SE NW

GEOLOGY

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Avg	
Herrin					Underground

Geologic Problems Reported:

PRODUCTION HISTORY

Company	Mine Name	Years	Production (tons)
Unidentified mines near Coal Hollow		before 1876	Unknown *

* Production, years of operation, and ownership is not known for these mines that operated before the Coal Reports were published in 1882.

Last reported production:

SOURCES OF DATA

Source Map	Date	Original Scale	Digitized Scale	Map Type
Atlas of Illinois	1876	1:158400	1:75429	Secondary source

Annotated Bibliography (data source, brief description of information)

Atlas of Illinois, 1876, Warner & Beers Company - Shaft locations.

OTHER MINES SHOWN ON DEPUE QUADRANGLE

Mine Index 6342 SE NE NW 31-T16N-R11E, shaft source: ISGS field notes (G. H. Cady, 5-7-1912) & ISGS map library, 4107 d5.6-40, sheet 6 (G. H. Cady's field map, a 15-minute USGS topographic map)

INDEX OF MINES IN THE DEPUE QUADRANGLE

Bierman	11
Bloom & Cox	11
Chicago, Wilmington & Vermilion Coal Company, Loceyville Mine	9
Chicago, Wilmington & Vermilion Coal Company, Seatonville Mine	10
Coal Hollow Coal Company	11
Cox (Bloom & Cox)	11
Griffith (John)	11
Griffith (John) & Son	11
Heathcock (George)	11
Locey (George H.)	9
Marquette Third Vein Coal Company	9
Marshall (A. O.)	9
Martin (Eugene)	11
Prairie State Coal Company	12
Saunders (Earl)	11
Seaton Brothers	10
Seatonville Mine	10
Spring Valley Coal Company, No. 4 Mine	10
St. Paul Coal Company, No. 1 Mine	12
Vane (Joseph)	11

