

# Coal Mines in Illinois Keensburg Quadrangle

## Wabash County, Illinois

### Friendsville Coal

This map accompanies the Coal Mines Directory for the Keensburg Quadrangle and map of mines in the Springfield Coal, Keensburg Quadrangle. Consult the directory for a complete explanation of the information shown on this map.

- Mining Method**
- Room & Pillar (RP)
  - Room & Pillar Basic (RPB)
  - Modified Room & Pillar (MRP)
  - Room & Pillar Panel (RPP)
  - Blind Room & Pillar (BRP)
  - Checkerboard Room & Pillar (CRP)
  - High Extraction Retreat (HER)
  - Longwall (LW)
  - Underground, Method Unknown
  - Strip Mine
  - Auger Mine
  - General Area of Mining

- Source of Mine Outline**
- Final Mine Map
  - Not Final Mine Map
  - Undated Mine Map
  - Incomplete Mine Map
  - Secondary Source Map

- Tipple, Shaft, Slope, Drift Locations**
- Strip Mine Tipple - Active
  - Strip Mine Tipple - Abandoned
  - Mine Shaft - Active
  - Mine Shaft - Abandoned
  - Mine Slope - Active
  - Mine Slope - Abandoned
  - Mine Drift - Active
  - Mine Drift - Abandoned
  - Air Shaft
  - Uncertain Location
  - Uncertain Type of Opening

**Mine Annotation**  
(space permitting)  
Company  
Mine Name  
ISGS Index No., Years of Operation

**Disclaimer**  
Please check the Coal Section at the Illinois State Geological Survey's web site at <http://www.isgs.illinois.edu> for the most up-to-date version of these products.

Note that each quadrangle scale mined-out area map requires the use of the associated text directory for full explanation of map features and mine attributes. Also note that some quadrangles have multiple seams of mining and therefore more than one map may be available for a particular quadrangle. Please take care to check for multiple maps, as extensive mining may exist in the other seams.

The maps and digital files used for these studies were compiled from data obtained from a variety of public and private sources and have varying degrees of completeness and accuracy. This compilation map presents a reasonable interpretation of the geology of the area and is based on available data. Locations of some mine features may be offset by 500 feet or more due to errors in the original source maps, the compilation process, digitizing, or a combination of these factors. These data are not intended for use in site-specific screening or decision-making. Use of these documents does not eliminate the need for detailed studies to fully understand the geology of a specific site. The Illinois State Geological Survey, Prairie Research Institute, or the University of Illinois make no guarantee, expressed or implied, regarding the correctness of the interpretations presented in this data set and accept no liability for the consequences of decisions made by others on the basis of the information presented here.


These maps were designed for use at 1:24,000. Enlarging the map may reduce accuracy, as the original scale of the source maps used to compile the outlines shown varies from 1:400 to 1:150,000, and some mine locations are known only from text descriptions. See the accompanying mine directory for the original scale of the source map used for a specific mine to check accuracy of a given portion of the map. Areas with no mines shown may still be undetermined; see the unlocated mines list at the back of each mine directory.

The image of the U.S.G.S. topographic base map was projected from the original UTM to Lambert Conformal Conic.



Prairie Research Institute  
Illinois State Geological Survey  
615 E. Peabody Dr.  
Champaign, IL 61820

Mine Outlines Compiled by  
Alan R. Myers  
February 10, 2012



# Coal Mines in Illinois Keensburg Quadrangle

## Wabash County, Illinois

### Springfield Coal

This map accompanies the Coal Mines Directory for the Keensburg Quadrangle and map of mines in the Friendsville Coal, Keensburg Quadrangle. Consult the directory for a complete explanation of the information shown on this map.

- Mining Method**
- Room & Pillar (RP)
  - Room & Pillar Basic (RPB)
  - Modified Room & Pillar (MRP)
  - Room & Pillar Panel (RPP)
  - Blind Room & Pillar (BRP)
  - Checkerboard Room & Pillar (CRP)
  - High Extraction Retreat (HER)
  - Longwall (LW)
  - Underground, Method Unknown
  - Strip Mine
  - Auger Mine
  - General Area of Mining
- Source of Mine Outline**
- Final Mine Map
  - Not Final Mine Map
  - Undated Mine Map
  - Incomplete Mine Map
  - Secondary Source Map
- Mine Annotation**  
(space permitting)
- Company
- Mine Name
- ISGS Index No., Years of Operation

- Tipple, Shaft, Slope, Drift Locations**
- Strip Mine Tipple - Active
  - Strip Mine Tipple - Abandoned
  - Mine Shaft - Active
  - Mine Shaft - Abandoned
  - Mine Slope - Active
  - Mine Slope - Abandoned
  - Mine Drift - Active
  - Mine Drift - Abandoned
  - Air Shaft
  - Uncertain Location
  - Uncertain Type of Opening

- Location**
- Strip Mine Tipple - Active
  - Strip Mine Tipple - Abandoned
  - Mine Shaft - Active
  - Mine Shaft - Abandoned
  - Mine Slope - Active
  - Mine Slope - Abandoned
  - Mine Drift - Active
  - Mine Drift - Abandoned
  - Air Shaft
  - Uncertain Location
  - Uncertain Type of Opening

**Mine Annotation**  
(space permitting)

Company

Mine Name

ISGS Index No., Years of Operation

**Disclaimer**

Please check the Coal Section at the Illinois State Geological Survey's web site at <http://www.isgs.illinois.edu> for the most up-to-date version of these products.

Note that each quadrangle scale mined-out area map requires the use of the associated text directory for full explanation of map features and mine attributes. Also note that some quadrangles have multiple seams of mining and therefore more than one map may be available for a particular quadrangle. Please take care to check for multiple maps, as extensive mining may exist in other seams.

The maps and digital files used for these studies were compiled from data obtained from a variety of public and private sources and have varying degrees of completeness and accuracy. This compilation map presents a reasonable interpretation of the geology of the area and is based on available data. Locations of some mine features may be offset by 500 feet or more due to errors in the original source maps, the compilation process, digitizing, or a combination of these factors. These data are not intended for use in site-specific screening or decision-making. Use of these documents does not eliminate the need for detailed studies to fully understand the geology of a specific site. The Illinois State Geological Survey, Prairie Research Institute, or the University of Illinois make no guarantee, expressed or implied, regarding the correctness of the interpretations presented in this data set and accept no liability for the consequences of decisions made by others on the basis of the information presented here.

These maps were designed for use at 1:24,000. Enlarging the map may reduce accuracy, as the original scale of the source maps used to compile the outlines shown varies from 1:400 to 1:150,000, and some mine locations are known only from text descriptions. See the accompanying mine directory for the original scale of the source maps used for a specific mine to check accuracy of a given portion of the map. Areas with no mines shown may still be undetermined; see the unlocated mines list at the back of each mine directory.

The image of the U.S.G.S. topographic base map was projected from the original UTM to Lambert Conformal Conic.



Prairie Research Institute  
Illinois State Geological Survey  
615 E. Peabody Dr.  
Champaign, IL 61820

Mine Outlines Compiled by  
Alan R. Myers  
February 10, 2012

# **DIRECTORY OF COAL MINES IN ILLINOIS**

## **7.5-MINUTE QUADRANGLE SERIES**

### **KEENSBURG QUADRANGLE**

#### **WABASH COUNTY**

Alan R. Myers & C. Chenoweth



2012

Prairie Research Institute  
William W. Shilts, Executive Director  
**ILLINOIS STATE GEOLOGICAL SURVEY**  
E. Donald McKay III, Director

Natural Resources Building  
615 East Peabody Drive  
Champaign, Illinois 61820

Phone 217-244-4610  
Fax 217-333-2830



This material is based upon work supported by the Illinois Department of Transportation. Any opinions, findings, and conclusions or recommendations expressed in this publication are those of the authors and do not necessarily reflect the views of the Illinois Department of Transportation.

**Cover photo** Track-mounted duckbill loading machine at a Peabody Coal Company mine, ca. 1915.

DISCLAIMER: The accuracy and completeness of mine maps and directories vary with the availability of reliable information. Maps and other information used to compile this mine map and directory were obtained from a variety of sources and the accuracy of some of the original information cannot be verified. Consequently, the Illinois State Geological Survey (ISGS) cannot guarantee the mine maps are free of errors and disclaims any responsibility for damages that may result from actions or decisions based on them.

The ISGS updates the maps and directories periodically, and welcomes any new information or corrections. Please contact the Coal Section of the ISGS at the address shown on the title page of this directory, or telephone (217) 244-4610.

© 2012 The Board of Trustees of the University of Illinois. All rights reserved.  
For permission information, contact the Illinois State Geological Survey.

## CONTENTS

INTRODUCTION .....	1
MINING IN THE KEENSBURG QUADRANGLE .....	1
PART I EXPLANATION OF MAP AND MINE SUMMARY SHEET .....	2
INTERPRETING THE MAP .....	2
Mine Type and Mining Method .....	2
Source Maps .....	3
Points and Labels .....	3
INTERPRETING A MINE SUMMARY SHEET .....	6
REFERENCES .....	8
PART II DIRECTORY OF MINES IN THE KEENSBURG QUADRANGLE .....	9
MINE SUMMARY SHEETS .....	9
Mine Index 921	
Wabash Mine Holding Company, Wabash Mine .....	9
Mine Index 3899	
New Bluff Coal Company, New Bluff Mine .....	10
Mine Index 3900	
Briar Hill Coal Company, Briar Hill Mine .....	11
Mine Index 3901	
Bluff Coal Company, Bluff Mine .....	12
OTHER MINES SHOWN ON KEENSBURG QUADRANGLE .....	13
Mine Index 7478 .....	13
INDEX OF MINES IN THE KEENSBURG QUADRANGLE .....	14



## **INTRODUCTION**

Coal has been mined in 76 counties of Illinois. More than 7,400 coal mines have operated since commercial mining began in Illinois about 1810; fewer than 30 are currently active. To detail the extent and location of coal mining in Illinois, the Illinois State Geological Survey (ISGS) has compiled maps and directories of known coal mines. The ISGS offers maps at a scale of 1:100,000 and accompanying directories for each county in which coal mining is known to have occurred. Maps at a scale of 1:24,000 and accompanying directories, such as this, are available for selected quadrangles. Contact the ISGS for a list of these quadrangles.

These larger scale maps show the approximate positions of mines in relation to surface features such as roads and water bodies, and indicate the mining method used and the accuracy of the mine boundaries. The maps are useful for locating mine boundaries relative to specific properties and for assessing the potential for subsidence in an area. Mine boundaries compiled from final mine surveys are generally shown within 200 feet of their true position. As a result of poor cartographic quality and inaccuracies in the original mine surveys, boundaries of some older mines may be mislocated on the map by 500 feet or more. Original mine maps should be consulted in situations that require precise delineation of mine boundaries or internal workings of mined areas.

This directory serves as a key to the accompanying mine map and provides basic information on the coal mines in the quadrangle. The directory is composed of two parts. Part I explains the symbols and patterns used on the accompanying map and the summary data presented for each mine. Part II numerically lists the mines in the quadrangle and summarizes the geology and production history of each mine. Total production for the mine, not the portion in the quadrangle, is given.

## **MINING IN THE KEENSBURG QUADRANGLE**

The Friendsville Coal was mined between 1920 and 1940. It was generally between 30 and 60 feet deep and accessed by shaft, except at a mine in the northern part of the Keensburg Quadrangle (mine index 7478) that was a surface mine whose dates of operation are not known. The Friendsville Coal averaged 3.5 feet thick, and the mines were less than 10 acres.

In recent years (1973 to 2007), the Springfield Coal was mined at a depth of almost 800 feet. The Wabash Mine (mine index 921) worked over 14,000 acres in coal that averaged 6.5 feet thick.

## PART I EXPLANATION OF MAP AND MINE SUMMARY SHEET

### INTERPRETING THE MAP

The map accompanying this directory shows the location of coal mines known to be present in the quadrangle. The map, corresponding to a U.S. Geological Survey (USGS) 7.5-minute quadrangle, covers an area bounded by lines of latitude and longitude 7.5-minutes apart. In Illinois, a quadrangle is approximately 6.5 miles east to west and 8.5 miles north to south, an area of about 56 square miles. The USGS generally offers one map of mines per quadrangle. In some areas where extensive mining occurred in two or more overlapping seams, separate maps are compiled for mines in each seam to maintain readability of the map.

#### **Mine Type and Mining Method**

The mine type is indicated on the map by pattern color: green represents surface mines; red and yellow represent underground mines. The red patterns are used for areas of underground mining that are documented by a primary or secondary source map. A yellow pattern is used for cases where no map of the mine workings is available, but a general area of mining can be inferred from property maps or production figures. The patterns indicate the main mining methods used in underground mines. The methods are (1) room and pillar and (2) high extraction. The method used gives some indication of the amount and pattern of coal extraction within each mined area, and has some influence on the timing and type of subsidence that can occur over a mine.

The following discussion and illustrations of mining methods are based on Guither et al. (1984).

In room-and-pillar mines, coal is removed from haulage-ways (entries) and selected areas called rooms. Pillars of unmined coal are left between the rooms to support the roof. Depending on the size of rooms and pillars, the amount of coal removed from the production areas will range from 40% to 70%.

**Room and Pillar** - mining is divided into six categories:

- room-and-pillar basic (RPB, fig. 1A), an early method that did not follow a preset mining plan and therefore resulted in very irregular designs;
- modified room and pillar (MRP, fig. 1B);
- room-and-pillar panel (RPP, fig. 1C);
- blind room and pillar (BRP, fig. 1D);
- checkerboard room and pillar (CRP, fig. 1E);
- room and pillar (RP), a classification used when the specific type of room-and-pillar mining is unknown.

Blind and checkerboard are the most common types of room-and-pillar mining used in Illinois today. The knowledge of room-and-pillar mining methods gives a trained engineer information on the nature of subsidence that may occur. A more extensive discussion of subsidence can be found in Bauer et al. (1993).

**High-extraction** These mining methods are subdivided into high-extraction retreat (HER, Fig 1F) and longwall (LW, Fig 1G, 1H). In these methods, much of the coal is removed within well defined areas of the mine. Subsidence of the surface above these areas occurs within weeks. Once the subsidence activity ceases, the potential for further movement over these areas is low; however, subsidence may continue for several years after mining.

High-extraction retreat mining is a form of room-and-pillar mining that extracts most of the coal. Rooms and pillars are developed in the panels, and the pillars are then systematically removed (fig. 1F).

In early (pre-1960) longwall mines, mining advanced in multiple directions from a central shaft (fig. 1G). Large pillars of coal were left around the shaft, but all coal was removed beyond these pillars. Miners placed rock and wooden props and cribs in the mined-out areas to support the mine roof. The overlying rock gradually settled onto these supports, thus producing subsidence at the surface. In post-1959 longwall mines, room-and-pillar methods have been used to develop the main entries of the mine and panel areas. Modern longwall methods extract 100 percent of the coal in the panel areas (fig. 1H).

## SOURCE MAPS

Mine outlines depicted on the map are, whenever possible, based on maps made from original mine surveys. The process of compiling and digitizing the quadrangle map may produce errors of less than 200 feet in the location of mine boundaries. Larger errors of 500 feet or more are possible for mines that have incomplete or inaccurate source maps.

Because of the extreme complexity of some mine maps, detailed features of mined areas have been omitted. The digitized mine boundary includes the exterior boundary of all rooms or entries that were at least 80 feet wide or protruded 500 feet from the main mining area. Unmined areas between mines are shown if they are at least 80 feet wide; unmined blocks of coal within mines are shown if they are at least 400 feet on each side. Original source maps should be consulted when precise information on mine boundaries or interior features is needed.

The mine summary sheet lists the source maps used to determine each mine outline. The completeness of map sources is indicated on the map by a line symbol at the mine boundary. Source maps are organized in five categories.

**Final mine map** The mine outline was digitized from an original map made from mine surveys conducted within a few months after production ceased. The date of the map and the last reported production are listed on the summary sheet.

**Not a final map** The mine is currently active or the mine outline was made from a map based on mine surveys conducted more than a few months before production ceased. This implies the actual mined-out area is probably larger than the outline on the map. The mine summary sheet indicated the dates of source maps and the last reported production, as well as the approximate tonnage mined between these two dates (if the mine is abandoned). The summary sheet also lists the approximate acreage mined since the date of the map and, in some cases, indicates the area where additional mining may have taken place. This latter information is determined by locating on the map the active faces relative to probable boundaries of the mine property.

**Undated map** The source map was undated, so it may or may not be based on a final mine survey. When sufficient data are available, the probable acreage of the mined area is estimated from reported production, average seam thickness and a recovery rate comparable to other mines in the area. This information is listed in the summary sheet for the mine.

**Incomplete map** The source map did not show the entire mine. The summary sheet indicates the missing part of the mine map and the acreage of the unmapped area, which is estimated from the amount of coal known to have been produced from the mine.





**Secondary source map** The original mine map was not found so the outline shown was determined from secondary sources (e.g., outlines from small-scale regional maps published in other reports). The summary sheet describes the secondary sources.

## POINTS AND LABELS





The locations of all known mine openings (shafts, slopes, and drifts) and surface mine tipples are plotted on the map. Tipples are areas where coal was cleaned, stockpiled, and loaded for shipping.

Only openings or tipples are plotted for mines without source maps. If the precise locations of these features are unknown, a special symbol is used to indicate the approximate location of the mine.


Each mine on the map is labeled with the names of the mine and operating company, ISGS mine index number, and years of operation (if known) if space permits. A seam designation is given on maps where more than one seam was mined. For a mine that operated under more than one name, only the most recent name is generally given. When a mine changed names or ownership shortly before closing, an earlier name is listed. All company and mine names are listed on the mine summary sheet in the directory, under the production history segment.



**Figure 1** Mining methods: (A) room-and-pillar basic (RPB), (B) modified room and pillar (MRP), (C) room-and-pillar panel (RPP), (D) blind room and pillar (BRP).



**Figure 1 (cont.)** Mining methods: (E) checkerboard room and pillar (CRP), (F) high extraction retreat (HER), (G) early (pre-1960) longwall, (H) post-1959 longwall



**Figure 2** Generalized stratigraphic section, showing approximate vertical relations of coals in Illinois.

## INTERPRETING A MINE SUMMARY SHEET

The mine summary sheet is arranged numerically by mine index number. Index numbers are shown on the map and in the mine listing. The mine summary sheet provides the following information (if available).

**Company and mine name** The last company or owner of the mine is used, unless no production was recorded for the last owner. In that case, the penultimate owner is listed. Mines often have no specific name; in these cases, the company name is also used as the mine name.

**Type** *Underground* denotes a subsurface mine in which the coal was reached through a shaft, slope, or a drift entry. *Surface* denotes a surface, open pit or strip mine.

**Total mined-out acreage shown** The total acreage of the mined area mapped, including any acreage mined on adjacent quadrangles, is calculated from the digitized outline of the mine. The acreage of large barrier pillars depicted on the map is excluded from the mined-out acreage. Small pillars not digitized are included in the acreage calculation. If the mine outline is not based on a final mine map, the acreage is followed by an estimate of additional acres that may have been mined. The estimate is determined from reported mine production, approximate thickness of the coal, and recovery rates calculated from nearby mines that used similar mining methods.

## SHAFT, SLOPE, DRIFT OR TIPPLE LOCATIONS

**Shaft, slope, drift, or tippie locations** Locations of all known former entry points to underground mines or the location of coal cleaning, tippie, and shipping equipment used by the mine's facility are listed. The location is described in terms of county, township and range (Twp-Rge), section, and location within the section by quarters. NE SW NW, for instance, would describe the location in the northeast quarter of the southwest quarter of the northwest quarter. When sections are irregular in size, the quarters remain the same size and are oriented (or "registered") from the southeast corner of the section. Approximate footage from the section lines (FEL = from east line, FNL = from north line, for example) is given when that information is known; this indicates a surveyed location and is not derived from maps. Entry points are also plotted on the map and coded for the type of entry or tippie. A mine opening may have had many purposes during the life of the mine. Old hoist shafts are often later used for air and escape shafts; this information is included in the directory when known. The tippie for underground mines was generally located near the main shaft or slope. At surface mines, coal was sometimes hauled to a central tippie several miles from the mine pit.

## GEOLOGY

**Seam(s) mined** The name of the coal seam(s) mined is listed, if known. If multiple seams were mined, they are all listed, although the mined-out area for each seam may be shown on separate maps. Figure 2 shows the stratigraphic section of the coal-bearing interval in Illinois, and the vertical relations among the coals.

**Depth** The depth to the top of the seam in the vicinity of the shaft is listed, if known. The depth is determined from notes made by geologists who visited the mine during its operation or from drill hole data in ISGS files. Depth generally varies little over the extent of a mine; however, reported depths for an individual mine may vary. Depth for surface-mined coals varies, and is usually represented as a range.

**Thickness** The approximate thickness of the mined seam is shown, if known. Thickness also comes from notes of geologists who visited the mine during its operation or from borehole data in ISGS files. Minimum, maximum, and average thicknesses are given when this information is available.

**Mining method** The principal mining method used at the mine (figs. 1A-H) is listed. See the mining methods section at the beginning of this directory for a discussion of this parameter.

**Geologic problems reported** Any known geologic problems, such as faults, water seepage, floor heaving, and unstable roof, encountered in the mine are reported. This information is from notes made by ISGS geologists who visited the mine, or from reports by mine inspectors published by the Illinois Department of Mines and Minerals, or from the source map(s). Geologic problems are not reported for active mines.

## PRODUCTION HISTORY

**Production history** Tons of coal produced from the mine by each mine owner are totaled. When the source map used for the mine outline is not a final mine map, the tonnage produced since the date of the map is identified. For mines that extend into adjacent quadrangles, the tonnage reported includes areas mined in adjacent quadrangles.

## SOURCE OF DATA

**Source map** This section lists information about the map(s) used to compile the mine outline and the locations of tipples and mine openings. In some cases more than one source map was used. For example, a map drawn before the mine closed may provide better information on original areas of the mine than a later map. When more than one map was used, the bibliography section explains what information was taken from each source.

**Date** The date of the most recent mine survey listed on the source map is reported.

**Original scale** The original scale of the source map is listed. Many maps are photo-reductions and are no longer at their original scale. The original scale gives some indication of the level of detail of the mine outline and the accuracy of the mine boundary relative to surface features. Generally, the larger the scale, the greater the accuracy and detail of the mine map. Mine outlines taken from source maps at scales smaller than 1:24,000 may be highly generalized and may well be inaccurately located with respect to surface features.

**Digitized scale** The scale of the digitized map is reported. The scale may be different from that of the original source map. In many cases the digitized map was made from a photo-reduction of the original source map, or the source map was not in a condition suitable for digitizing and the mine boundaries were transferred to another base map.

**Map type** Source maps are classified into five categories to indicate the probable completeness of the map. See discussion of source maps in the previous section.

**Annotated bibliography** Sources that provide information about the mine are listed, with the data taken from each source. Some commonly used sources are described below. Full bibliographic references are given for all other sources. Unless otherwise noted, all sources are available for public inspection at the ISGS.

**Coal Reports** Published since 1881, these reports contain tabular data on mine ownership, production, employment, and accidents. Some volumes include short descriptions made by mine inspectors of physical features and conditions in selected mines.

**Directory of Illinois Coal Mines** This source is a compilation of basic data about Illinois coal mines, originally gathered by ISGS staff in the early 1950s. Sources used for this directory are undocumented, but they are primarily Illinois Department of Mines and Minerals annual reports, ISGS mine notes, and coal company officials.

**ENR Document 85/01**, Guither, H. D., J. K. Hines, and R. A. Bauer, 1985 The Economic Effect of Underground Mining Upon Land Used for Illinois Agriculture: Illinois Department of Energy and Natural Resources Document 85/01, 185 p.

**Microfilm map** The U.S. Bureau of Mines maintains a microfilm archive of mine maps. A microfilm file for Illinois is available for public viewing at the ISGS.

*Mine notes* ISGS geologists have visited mines or contacted mine officials throughout the state since the early 1900s. Notes made during these visits range from brief descriptions of the mine location to long narratives (including sketches) of mining conditions and geology.

*Federal Land Bank of St. Louis, Preliminary Reports on Subsidence Investigations* Mining engineers working for the Federal Land Bank of St. Louis mapped areas of subsidence due to coal mining in the early 1930s. These reports often include county maps of mine properties with mined-out areas including shaft locations, as well as subsidence areas.

## **REFERENCES**

Bauer, R. A., B. A. Trent, and P. B. Dumontelle, 1993, Mine Subsidence in Illinois: Facts for the Homeowner Considering Insurance, Illinois State Geological Survey, Environmental Geology Note 144, 16p.

Guither, H. D., J. K. Hines, and R. A. Bauer, 1985, The Economic Effects of Underground Mining Upon Land Used for Illinois Agriculture, Illinois Department of Energy and Natural Resources Document 85/01, 185p.

## PART II DIRECTORY OF MINES IN THE KEENSBURG QUADRANGLE

### MINE SUMMARY SHEETS

A summary sheet on the geology and production history of each mine in the Keensburg Quadrangle is provided. These summary sheets are arranged numerically by mine index number. Consult Part I for a complete explanation of the data listed in the summary sheet.

#### Mine Index 921

#### Wabash Mine Holding Company, Wabash Mine

Type: Underground Total mined-out acreage shown: 14,069 The outline shown on the accompanying map extends into Indiana.

### SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS

Type	County	Township-Range	Section	Quarters-Footage
Main slope	Wabash	2S 13W	10	NW SW SE
Air shaft	Wabash	2S 13W	10	SE SW SE
Air shaft	Wabash	2S 13W	15	SE NE NW
Air shaft	Wabash	2S 13W	19	approx. 500 FSL, 1350 FWL
Air shaft	Wabash	2S 14W	24	SW SE SE
Shaft	Wabash	2S 13W	27	SW NE NW
Air shaft	Wabash	2S 13W	27	NW NW NW

### GEOLOGY

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Avg	
Springfield	796		8.0	6.5	CRP

Geologic Problems Reported: The Wabash Mine was within the Wabash Valley Fault System, and was bordered on the west by the New Harmony Fault with more than 60 feet of displacement. A southwest-northeast trending fault can be discerned disrupting the mining pattern shown on the Keensburg Quadrangle. The northern part of the mine was within a mile of the Galatia Channel, which was contemporaneous with coal deposition. Consequently, some areas of split coal and other related features were seen in the mine, in the northern, western, and eastern parts. The roof was a medium gray, well-bedded and laminated silty shale. Water was seen at the interface of the coal and the roof. Pyrite was seen in bands and as cleat fillings.

### PRODUCTION HISTORY

Company	Mine Name	Years	Production (tons)
Amax Coal Company	Wabash	1973-1997	60,545,992
Wabash Mine Holding Company	Wabash	1998-2007	16,391,924
			76,937,916

Last reported production: 2007

### SOURCES OF DATA

Source Map	Date	Original Scale	Digitized Scale	Map Type
Coal Section files, 6-385	1-1-2008	1:12000	1:12000	Final

#### Annotated Bibliography (data source, brief description of information)

Coal Reports - Production, ownership, years of operation.

Directory of Illinois Coal Mines (Wabash County) - Mine names, mine index, ownership, years of operation.

Mine notes (Wabash County) - Mine type, slope location, seam, depth, thickness, geologic problems.

Company map, Coal Section files, 6-385 - Slope & shaft locations, mine outline, mining method, geologic problems.

**Mine Index 3899****New Bluff Coal Company, New Bluff Mine**

Type: Underground Total mined-out acreage shown: 3 Production indicates approximately 2 acres were mined. The outline shown on the accompanying map is larger than expected for the reported production and may indicate that the mine operated during the period (1930-1932) when the Coal Report did not list production for mines producing less than 1,000 tons per year. Production indicates less than 1 acre was mined after the map date.

**SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS**

Type	County	Township-Range	Section	Quarters-Footage
Main shaft	Wabash	2S 13W	20	SE NE NE
Air shaft	Wabash	2S 13W	20	SE NE NE

**GEOLOGY**

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Avg	
Friendsville	50-60			3.5-4.0	MRP

Geologic Problems Reported: The roof was fossiliferous shale that may have had a thin limestone above.

**PRODUCTION HISTORY**

Company	Mine Name	Years	Production (tons)
New Bluff Coal Company *	New Bluff	1933-1936	3,592
New Bluff Coal Company	New Bluff	1933-1936	<u>2,215</u> **
			5,807

\* Operator Elvia Stokes

\*\* Production after map date

Last reported production: 1936

**SOURCES OF DATA**

Source Map	Date	Original Scale	Digitized Scale	Map Type
Microfilm, document 353022	1935	1:1200	1:1489	Not final

Annotated Bibliography (data source, brief description of information)

Coal Reports - Production, ownership, years of operation.

Directory of Illinois Coal Mines (Wabash County) - Mine names, mine index, ownership, years of operation.

Mine notes (Wabash County) - Mine type, shaft location, depth, thickness.

ISGS field notes (Wabash County) - Mine type, depth, thickness, geologic problems.

Microfilm map, document 353022, reel 03141, frame 191 - Shaft locations, mine outline, mining method.

**Mine Index 3900****Briar Hill Coal Company, Briar Hill Mine**

Type: Underground    Total mined-out acreage shown: 10    Production indicates less than 1 acre was mined after the map date.

**SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS**

Type	County	Township-Range	Section	Quarters-Footage
Main shaft	Wabash	2S 13W	21	NE SW NW
Air shaft	Wabash	2S 13W	21	NE SW NW

**GEOLOGY**

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Avg	
Friendsville	60			3.5	MRP

Geologic Problems Reported:

**PRODUCTION HISTORY**

Company	Mine Name	Years	Production (tons)
Briar Hill Coal Company	Briar Hill	1933-1936	20,680
W. V. Brown	Briar Hill	1937-1938	8,086
Briar Hill Coal Company	Briar Hill	1939-1939	2,004
Briar Hill Coal Company	Briar Hill	1939-1940	2,730 *
			33,500

\* Production after map date

Last reported production: 1940

**SOURCES OF DATA**

Source Map	Date	Original Scale	Digitized Scale	Map Type
Microfilm, document 353026	5-1939	1:1200	1:1200	Not final

Annotated Bibliography (data source, brief description of information)

Coal Reports - Production, ownership, years of operation.

Directory of Illinois Coal Mines (Wabash County) - Mine names, mine index, ownership, years of operation.

Mine notes (Wabash County) - Mine type, shaft location, seam, depth, thickness.

Microfilm map, document 353026, reel 03141, frame 195 - Shaft locations, mine outline, mining method.

**Mine Index 3901**  
**Bluff Coal Company, Bluff Mine**

Type: Underground    Total mined-out acreage shown: None; production indicates approximately 4 acres were mined.

**SHAFT, SLOPE, DRIFT or TIPPLE LOCATIONS**

Type	County	Township-Range	Section	Quarters-Footage
Main shaft	Wabash	2S 13W	21	SE NW NW

**GEOLOGY**

Seam(s) Mined	Depth (ft)	Thickness (ft)			Mining Method
		Min	Max	Avg	
Friendsville	47	3.0	4.0	3.5	Underground

Geologic Problems Reported: The coal occasionally contained 4 to 8 inches of black jack or limestone lenses. The coal had thick calcite facings.

**PRODUCTION HISTORY**

Company	Mine Name	Years	Production (tons)
Bluff Coal Company	Bluff	1924-1930 *	<u>12,147</u> 12,147

\* Mines producing less than 1,000 tons per year were not listed in the Coal Reports from 1930 to 1933. This mine may have operated later than 1930.

Last reported production: 1930

**SOURCES OF DATA**

Source Map	Date	Original Scale	Digitized Scale	Map Type
ISGS map library, 4103.W31 i5.1-4	1927	1:62500	1:62500	Secondary source

Annotated Bibliography (data source, brief description of information)

Coal Reports - Production, ownership, years of operation.  
 Directory of Illinois Coal Mines (Wabash County) - Mine names, mine index, ownership, years of operation.  
 Mine notes (Wabash County) - Mine location, seam.  
 ISGS field notes (Wabash County) - Depth, thickness, geologic problems.  
 ISGS map library, 4103.W31 i5.1-4, work map of L. G. Henbest - Shaft location.

## **OTHER MINES SHOWN ON KEENSBURG QUADRANGLE**

Mine Index 7478 SW SE SW 2-T2S-R13W, surface, 100 by 100 yard area mined for local use source: ISGS field notes (J. M. Schopf, copied by G. H. Cady, 9-1942)

## INDEX OF MINES IN THE KEENSBURG QUADRANGLE

Amax Coal Company .....	9
Bluff Coal Company .....	12
Briar Hill Coal Company .....	11
Brown (W. V.) .....	11
New Bluff Coal Company .....	10
Stokes (Elvia) .....	10
Wabash Mine .....	9
Wabash Mine Holding Company .....	9

